

SAFESHIELD UL

DIMENSIONS (mm)
Max pane H: 1000
Min pane H: 400
Max pane W: 1800

WEIGHT

10mm polycarbonate 12kg per m2

RESISTANCE

Successfully tested to withstand manual attack from a variety of tools including various hammers and axe.

CONSTRUCTION

Horizontal metalwork will be polyester powder coated to match corporate colours. Screen frame constructed from mild steel and zinc plated. The screen is 10mm polycarbonate.

DATASHEET

SAFESHIELD UL

A polycarbonate screening system designed to offer protection to staff by hampering physical attack and vaulting of the counterwork by assailants, in operations with a minimal level security threat, whilst maintaining an open appearance and open-counter trading. This screen is an effective, cost efficient alternative to other high security alternatives that Safetell offers. Typical applications include petrol forecourts, convenience stores, retail, and fast food franchises.

MAIN FEATURES

- Able to accommodate multi-tiered and shaped counterwork
- Shapes and sizes tailored to suit client premises and corporate requirements
- Can be fitted to new or existing counterwork
- Transactions are usually made through vertical or horizontal transaction gaps between the glazing base and the counter surface.

OPTIONAL

- Can incorporate vertical and horizontal transaction gaps
- Counterwork can be supplied as part of the solution.



SERVICE &
MAINTENANCE
AVAILABLE

+44 (0) 1322 223 233

sales@safetell.co.uk safetell.co.uk

TECHNICAL DRAWINGS

EXAMPLE STANDARD COUNTER LAYOUT - PLAN VIEW


STAFF SIDE

RETURN **HAMPER**



PUBLIC SIDE

EXAMPLE STANDARD COUNTER LAYOUT - FRONT VIEW







WE ARE FULLY ACCREDITED













