Safetell
SECURITY | MAINTENANCE

DATASHEET

SAFEASSURE PLUS UJ

DIMENSIONS (mm)
Max pane H: 2000
Max pane W: 3000

WEIGHT (kg)
Determined by pane size

RESISTANCE
Manual attack resistance:
EN 356 P3A
EN 356 P5A
As a system in accordance with BS 5357

CONSTRUCTION
The system incorporates anti-physical attack glass, full steel frame and range of posts, catering for corners, angles and run joints.

Standard SafeAssure Plus UJ glazing is constructed using 10.3mm laminated glass.

Transactions are usually made through cash scoops recessed into the counter surface, although the system can be implemented with a horizontal transaction gap between the counter surface and glazing base if desired.

SAFEASSURE PLUS UJ

SafeAssure Plus UJ is a steel fully framed, manual attack resistant glazing system. Designed to provide staff and counter areas with protection from physical attack and robbery, with a high-quality aesthetic appearance in keeping with corporate and commercial environments. Typical applications include banks, police stations, retail, healthcare, councils and commercial buildings.

MAIN FEATURES

- High aesthetic quality, in keeping with existing environments
- Large pane size capability
- Tailored to suit premises and corporate look
- Can be fitted to existing or new counterwork
- Nationwide installation
- Complete secure-line solutions
- Centralised account management for standardised implementation

OPTIONAL

- Customer specified frame colours are available
- Standard and bespoke frame sizes are available
- Counterwork can be supplied as part of the solution
- Speech transfer and cash scoops are available
- Welded joints for increased security level
- A fully welded steel frame



SERVICE & MAINTENANCE AVAILABLE

+44 (0) 1322 223 233
sales@safetell.co.uk safetell.co.uk