HYDRON
Protective Coatings Ltd

www.hydronpc.co.uk
enquiries@hydronpc.co.uk

ISSUE: 04/01/2022

TECHNICAL DATA SHEET – HPC 99 NU-FLAME FR COLOURCOAT

DESCRIPTION:

Nu-Flame FR Colour Coat is a flame retardant paint finish.
Also used as a basecoat for use prior to multi-coloured finishes.

ADVANTAGES:

Being a water soluble product this is safe for internal applications. **Tested to BS 476 part 6 & 7 and satisfies Class '0' Requirements of current Building Regulations.**

USES:

For use on walls and ceilings.
Intermediate coat of the Nu-Flame Multi-coloured System.

COLOUR RANGE:

In any BS400 or RAL Shade.

PACK SIZE:

Single component product, supplied in 5 & 10 litre units.

COVERAGE RATE:

14 m² per litre

VOLUME SOLIDS

40%

DRYING TIME:

Touch:	2 Hours
Overcoat:	4 Hours

PREPARATION:

Ensure surfaces to be treated are clean, free from contamination and dry.

APPLICATION:

By brush/roller or Airless Spray

EQUIPMENT CARE:

All equipment should be cleaned with water immediately after use

STORAGE:

Store away from direct sunlight and sources of heat. Protect from frost.

SHELF LIFE:

12 months (in original sealed container).

HEALTH & SAFETY:

Refer to MSDS

Unit 7 Phoenix Road
Wednesfield
Wolverhampton
WV11 3PX, UK

TEL: +44(0) 1902 450 950

Data provided on this TDS is based on the best of our knowledge and experience, is given in good faith and should only be regarded as recommendations. No guarantee should be inferred and customers are advised to carry out their own tests under local conditions.