HYDRON
Protective Coatings Ltd

www.hydronpc.co.uk
enquiries@hydronpc.co.uk

ISSUE: 04/01/2022

TECHNICAL DATA SHEET – HPC 111 NU-FLAME FR ACRYLIC EGGSHELL

DESCRIPTION:

Nu-Flame FR Acrylic Eggshell is a water based flame retardant paint for new and previously painted surfaces, timber and concrete where an eggshell finish is required.

ADVANTAGES:

When Nu-Flame Acrylic FR Eggshell is used it provides a washable finish for interior use.
Tested to BS 476 part 6 & 7 and satisfies Class '0' Requirements of current Building Regulations

USES:

For use on doors, skirting and other timber finishes as well as painted surfaces and concrete to complement the Nu-Flame wall finishes

COLOUR RANGE:

In any BS400 or RAL Shade.

PACK SIZE:

Single component product, supplied in 5 & 10 litre units.

COVERAGE RATE:

14 m² per litre

VOLUME SOLIDS

40%

DRYING TIME:

Touch:	2 Hours
Overcoat:	6 Hours

PREPARATION:

Ensure surfaces to be treated are clean, free from contamination and dry.

APPLICATION:

By brush/roller or Airless Spray

EQUIPMENT CARE:

All equipment should be cleaned with water immediately after use

STORAGE:

Store away from direct sunlight and sources of heat. Protect from frost.

SHELF LIFE:

12 months (in original sealed container).

HEALTH & SAFETY:

Refer to MSDS

Unit 7 Phoenix Road
Wednesfield
Wolverhampton
WV11 3PX, UK

TEL: +44(0) 1902 450 950

Data provided on this TDS is based on the best of our knowledge and experience, is given in good faith and should only be regarded as recommendations. No guarantee should be inferred and customers are advised to carry out their own tests under local conditions.