

Resin Bound Permeable Surfacing

Recommended Specification for Terrabase Classic

Permeable Driveway (SUDS)

Typical Base Build Up

Surface Course

Hand applied and trowelled to a classic finish by Addagrip approved installers.



Typical depth of Terrabase Classic resin bound paving surface.


40mm layer of Addaset, Addabound or Terrabound

Terrabase Addagrid



Laid by Addagrip approved installers
Depth of Terrabase Addagrid 7.1mm

Terrabase Geofabric



Laid by Addagrip approved installers
Depth of Terrabase Geofabric 2.4mm



30mm Limestone layer of 6-10mm or 2-6mm aggregate

Sub-base

laid by others in well compacted layers to a minimum fall of 1.5%



A 150mm - 225mm layer of Type 3 granular sub-base

Sub-grade



NOTE: A suitable steel, wood, brick, stone or aluminium edging should be provided to ensure a neat edge detail. The maximum tolerance of the base should not exceed 3mm under a 1m straight edge. If existing sub-grade is silty, it may be necessary to stabilise it or partially replace it with sub base/granular capping layer. If there is danger of ponding, the sub base should be laid to falls. Total sub base depth will be dictated by loading and attenuation requirements.

Any advice, recommendation or information given by Addagrip Terraco Ltd is based on practical experience and is believed to be accurate at the time of publication, no liability or responsibility of any kind (including liability for negligence) is accepted in this respect by the company, its Servants, or Agents.

