

**////// TERRACO®**



# Handycoat®

READY-MIXED SKIMMING AND JOINTING  
COMPOUNDS FOR INTERIOR AND EXTERIOR USE



**Terraco Group** is a leading manufacturer of construction finishing materials, operating in Europe, Middle East, and Asia.

Terraco's Handycoat range of skimming and jointing compounds provides durable and evenly finished surfaces.



## Handycoat®

Best-in-class range of ready-mixed skimming and jointing compounds for interior and exterior use.



READY-MIXED



EASY TO APPLY

## EXTERIOR APPLICATION



**Handycoat Exterior**  
READY-MIXED EXTERIOR FILLER



**Handycoat Lite Exterior**  
LIGHTWEIGHT READY-MIXED  
EXTERIOR FILLER

## INTERIOR APPLICATION



**Handycoat Interior**  
INTERIOR READY-MIXED SKIMMING  
& JOINTING COMPOUND



**Handycoat EZ-Joint**  
INTERIOR READY-MIXED JOINTING  
COMPOUND



**Handycoat EZ-Roll**  
ROLLER APPLIED INTERIOR  
SKIMMING COMPOUND



**Handycoat EZ-Skim**  
INTERIOR READY-MIXED SKIMMING  
COMPOUND



**Handycoat LoDust**  
LOW DUSTING FILLER FOR  
INTERIOR USE



## Handycoat Exterior

### Ready-Mixed Exterior Filler

**Tough and Durable Finish.** Handycoat Exterior is formulated to ensure high strength, exceptional weather & crack resistance to provide a durable finish. It has elastic properties, does not flake off and retains its adhesion.

#### Areas of use:

- » Cementitious materials
- » Concrete
- » Precast concrete
- » Cement boards
- » Mineral boards
- » Exterior gypsum boards
- » Other common building surfaces

#### Perfect for:

- » Patching hairline cracks
- » Repairing damages in plaster & paint work
- » Jointing cement and mineral boards
- » Filling nail holes
- » Filling honeycomb in concrete substrate
- » Repairing defects in exposed concrete
- » Skimming of façade walls

WEATHER  
RESISTANT



EASY TO  
APPLY



EVEN SURFACE  
FOR PAINTING



DILUTION	With a small quantity of water if required
COVERAGE	0.5 -1.5kg/m <sup>2</sup> depending on substrate conditions
LAYER THICKNESS	Maximum thickness 1mm/layer
SPECIFIC GRAVITY	1.65 +/-0.05
COLOUR	White
PACKAGING	5kg and 25kg plastic pails
STORAGE	12 months in original unopened containers





## Handycoat Lite Exterior

### Lightweight Ready-Mixed Exterior Filler

Up to 30% lighter than conventional fillers. Handycoat Lite Exterior is formulated with special raw materials which make it lighter than conventional fillers without compromising volume.

#### Areas of use:

- » Cementitious materials
- » Concrete
- » Precast concrete
- » Cement boards
- » Exterior gypsum boards
- » Wood panel boards (OSB)
- » Other mineral boards
- » All common building surfaces

#### Perfect for:

- » Patching hairline cracks in walls, ceilings and soffits
- » Repairing damaged plasterwork and paintwork
- » Jointing cement and mineral boards
- » Filling nail holes
- » Filling honeycomb in concrete substrate
- » Repairing defects in woodwork and exposed concrete

HIGH  
STRENGTH



WEATHER  
RESISTANT



EASY TO  
SAND



DILUTION	With water if required
COVERAGE	0.3 -1.0kg/m2 depending on substrate conditions
LAYER THICKNESS	Maximum 2mm
SPECIFIC GRAVITY	1.10
COLOUR	White
PACKAGING	4kg and 18kg pails
STORAGE	12 months in original unopened containers





## Handycoat Interior

### Interior Ready-Mixed Skimming & Jointing Compound

Suitable for Most Building Surfaces. Handycoat Interior is made from a selected blend of acrylic polymers and precisely graded fillers to provide a uniform finish when repairing and touching up surfaces.

#### Areas of use:

- » Gypsum / Gypsum boards
- » Cementitious materials
- » Sprayplasters
- » Wood
- » Sand-cement renders
- » Cement boards
- » Most interior surfaces

#### Perfect for:

- » Skimming walls and ceilings
- » Conventional taping and jointing systems
- » Repairing damages, cracks or nail holes
- » Areas around door and window architraves

EASY TO APPLY



NO PRIMING REQUIRED



LOWER PAINT CONSUMPTION



DILUTION	With water if required
COVERAGE	1.6-1.7 kg/m <sup>2</sup> /mm
SPECIFIC GRAVITY	1.75
COLOUR	Off-white
STANDARD COMPLIANCE	ASTM C-475
PACKAGING	5kg and 25kg plastic pails
STORAGE	18 months in original unopened containers.





## Handycoat EZ-Joint

### Interior Ready-Mixed Jointing Compound

Developed for efficient jointing of gypsum boards. Handycoat EZ-Joint is specially formulated to provide superior bond for jointing with either paper tape or self-adhesive mesh.

#### Areas of use:

- » Gypsum boards
- » Interior cement boards
- » Concrete walls
- » Plastered concrete
- » Cementitious materials

#### Perfect for:

- » Gypsum board jointing
- » Fixing metal corner beading
- » Patching plaster cracks
- » Filling of cementitious surfaces
- » Skimming of walls and ceilings

LOW SHRINKAGE



EASY TO APPLY



EXCELLENT ADHESION



DILUTION	With water if required, up to 0.5 ltr/25 kg
COVERAGE	1.7 kg/m <sup>2</sup>
LAYER THICKNESS	Maximum thickness 3mm/layer
SPECIFIC GRAVITY	1.70
COLOUR	White
STANDARD COMPLIANCE	ASTM C-475
PACKAGING	5 and 25 kg plastic pails; 25 kg plastic bags
STORAGE	12 months in original unopened containers





## Handycoat EZ-Roll

### Roller Applied Interior Skimming Compound

Developed for roller application on most building surfaces, including sand/cement renders and gypsum boards. Handycoat EZ-Roll is especially suited for levelling existing textured walls and ceilings.

#### Areas of use:

- » Gypsum boards
- » Sand-cement renders
- » New masonry substrates
- » Existing textured and painted surfaces

#### Perfect for:

- » Levelling of existing textured surfaces
- » Skimming of walls and ceilings
- » Repairing old and new surfaces
- » For professional applicators and DIY enthusiasts

HIGH  
COVERAGE



EASY TO  
APPLY



EXCELLENT FOR  
LEVELLING



DILUTION	With water if required
COVERAGE	1.0 -1.5kg/m <sup>2</sup> depending on substrate conditions.
LAYER THICKNESS	Maximum thickness 2mm/layer
SPECIFIC GRAVITY	1.75
COLOUR	White
PACKAGING	5kg and 25kg plastic pails
STORAGE	18 months in original unopened containers





## Handycoat EZ-Skim

### Interior Ready-Mixed Skimming Compound

Developed for efficient skim coating. Handycoat EZ-Skim is specially formulated for fast and easy application on old and new surfaces prior to painting.

#### Areas of use:

- » Cementitious materials
- » Renders
- » Gypsum boards
- » Spray plasters
- » Wood
- » All common building surfaces

#### Perfect for:

- » Gypsum board skimming
- » Repairing damages in plaster and paint work
- » Touch up of interior surfaces
- » Filling nail holes
- » Around door profiles and skirtings

EASY TO  
APPLY &  
SAND



QUICK  
DRYING



NO  
FLAKING



DILUTION	With a small quantity of water if required
COVERAGE	0.5 -1.5 kg/m <sup>2</sup> depending on substrate conditions
LAYER THICKNESS	Maximum thickness 2mm/layer
SPECIFIC GRAVITY	1.70
COLOUR	Off-white
STANDARD COMPLIANCE	ASTM C-475
PACKAGING	5 and 25 kg plastic pails; 25 kg plastic bags
STORAGE	12 months in original unopened containers





## Handycoat LoDust

### Low Dusting Filler for Interior Use

Up to 80% lower dust while sanding. Handycoat LoDust is a specially formulated filler that significantly minimizes dust pluming while sanding.

#### Areas of use:

- » Cementitious materials
- » Renders
- » Gypsum boards
- » Spray plasters
- » Wood
- » All common building surfaces

#### Perfect for:

- » Gypsum board jointing & skimming
- » Repairing damages, hairline cracks in plaster and paint work
- » Touch up of interior surfaces
- » Filling nail holes
- » Around door profiles and skirtings

SPECIAL  
LOW DUSTING  
FORMULA



EASY TO  
APPLY &  
SAND



QUICK  
DRYING



DILUTION	With a small quantity of water if required
COVERAGE	0.5 -1.5 kg/m2 depending on substrate conditions
LAYER THICKNESS	1-4mm
SPECIFIC GRAVITY	1.75 +/- 0.05
COLOUR	White
STANDARD COMPLIACE	ASTM C- 475
PACKAGING	5kg and 25kg containers
STORAGE	12 months in original unopened containers



# Handycoat®

## **GENERAL SURFACE PREPARATION PROCEDURE:**

New Surface - ensure all dust, dirt and foreign matter are scraped and brushed away. Also ensure the surfaces are free from salts, oil, grease and ridges. All cracks, chips, voids and damages should be repaired/prefilled with Handycoat.

Old Surface - ensure the substrate is firm. First wash down the surface with a soda/water solution, rinse and allow to dry before repairing or applying Terraco Primer.

**FOR DETAILED USAGE INSTRUCTIONS, PLEASE REFER TO THE TECHNICAL DATA SHEET**

---

## **GENERAL JOINTING APPLICATION PROCEDURE:**

1. Apply a thin layer of Handycoat to the joint and embed the paper tape accordingly
2. When using self-adhesive mesh, apply the self-adhesive mesh directly to the joint and fill with Handycoat
3. Apply a further layer of Handycoat to smooth the surface
4. Cover the screws with Handycoat
5. Allow to dry fully and proceed for skimming

**FOR DETAILED USAGE INSTRUCTIONS, PLEASE REFER TO THE TECHNICAL DATA SHEET**

---

## **GENERAL SKIMMING/LEVELLING APPLICATION PROCEDURE:**

1. Apply Handycoat in a thin even layer
2. If a thick coat is necessary apply several thin layers
3. Allow to dry between layers
4. Lightly sand the final surface before painting

**FOR DETAILED USAGE INSTRUCTIONS, PLEASE REFER TO THE TECHNICAL DATA SHEET**



[www.terraco.com](http://www.terraco.com)

SWEDEN • UK • IRELAND • RUSSIA • TURKEY • ALGERIA • EGYPT  
JORDAN • UAE • THAILAND • VIETNAM • CHINA • KOREA