

//// TERRACO®



Handycoat® EZ-Skim

INTERIOR READY-MIXED SKIMMING COMPOUND



**IDEAL FOR
SKIMMING**

WHY CHOOSE HANDYCOAT EZ-SKIM?

EASY TO APPLY & SAND

Handycoat EZ-Skim is developed for experienced applicators and amateur decorators alike to repair and touch up surfaces in an easy and efficient way. It requires minimum sanding efforts to get a smooth and even surface for painting.

QUICK DRYING

The special acrylic binder formulation dries faster compared to conventional fillers resulting in faster application and saving time.

NO FLAKING

Handycoat EZ-Skim provides a vapor permeable surface which prevents moisture built-up behind the coating. Together with its high adhesion power, it prevents flaking thus reducing the need for repair.



Handycoat[®] EZ-Skim

Developed for efficient skim coating.

Handycoat EZ-Skim is a ready-to-use interior filler and board skimming compound for most building surfaces, including sand/cement renders and gypsum boards. Along with fast and easy application, it provides a high quality, even surface for painting.

Handycoat EZ-Skim is specially formulated for efficient skim coating of surfaces both old and new, prior to painting.



OTHER FEATURES AND BENEFITS

- High versatility for use on multiple substrates as filler and board skimming compound.
- Low Volatile Organic Compounds (VOC) content that is better for human health and environment.
- High coverage rate allows covering a larger surface area using the same amount of material resulting in cost savings.

AREAS OF USE

- Cementitious Materials
- Renders
- Gypsum Boards
- Spray Plasters
- Wood
- All Common Building Surfaces

HANDYCOAT EZ-SKIM IS PERFECT FOR

- Gypsum board skimming
- Repairing damages in plaster and paint work
- Touch up of interior surfaces
- Filling nail holes
- Around door profiles and skirtings



HOW TO USE

- 1 Apply the filler in a thin even layer
- 2 If a thick coat is necessary, apply several thin layers
- 3 Allow to dry between layers
- 4 Lightly sand the final surface before painting

*For detailed usage instructions, please refer to the Technical Data Sheet

TECHNICAL DATA

Dilution	With a small quantity of water if required
Coverage	0.5 -1.5 kg/m ² depending on substrate conditions
Layer Thickness	Maximum thickness 2mm/layer
Specific Gravity	1.70
Colour	Off-white
Standard Compliance	ASTM C-475
Packaging	5 and 25 kg plastic pails; 25 kg plastic bags
Storage	12 months in original unopened containers



www.terraco.com

SWEDEN • UK • IRELAND • RUSSIA • TURKEY • ALGERIA • EGYPT
SOUTH AFRICA • JORDAN • UAE • THAILAND • VIETNAM • CHINA • KOREA