

//// TERRACO®



Handycoat® LoDust

LOW DUSTING FILLER FOR INTERIOR USE

UP TO
80%
LOWER
DUST

WHY CHOOSE HANDYCOAT LODUST?

SPECIAL LOW DUST FORMULA

Handycoat LoDust has been formulated with a combination of acrylic polymers and specially graded fillers, with a focus in minimizing dust clouds by up to 80% compared to conventional fillers. The formulation ensures dust particles stick together and settle down on the floor instead of pluming upwards.

EASY TO APPLY AND SAND

Handycoat LoDust is developed to help applicators repair and touch up old or new interior building surfaces in an easy and efficient way. The product is easy to sand and provides a comfortable experience with a reduced interference from dust clouds.

QUICK DRYING

The special acrylic binder formulation dries faster compared to other conventional fillers enabling faster output and a quicker paint job completion.



Handycoat[®] LoDust

Up to 80% lower dust while sanding.

Handycoat LoDust is a specially formulated filler that significantly minimizes dust pluming while sanding. The formulation makes dust particles clump together and settle down on the floor ensuring they do not form a dust cloud.

Handycoat LoDust ensures efficient work completion by reducing the discomfort to vision and breathing caused by sanding dust. The product delivers a comfortable application experience.



OTHER FEATURES AND BENEFITS

- Higher flexibility for use on multiple substrates as skim coat or board jointing compound
- High adhesion power that prevents flaking thus significantly improving life of the system
- Applicable for up to 4mm thickness
- Vapour permeable that prevents moisture and mould related damage providing longevity
- Low Volatile Organic Compounds (VOC) content that is better for human health and the environment

AREAS OF USE

- Cementitious Materials
- Renders
- Gypsum Boards
- Spray Plasters
- Wood
- All Common Building Surfaces

HANDYCOAT LODUST IS PERFECT FOR

- Gypsum board jointing
- Gypsum board skimming
- Repairing damages, hairline cracks in plaster and paint work
- Touch up of interior surfaces
- Filling nail holes
- Around door profiles and skirtings



HOW TO USE

- 1 Apply the filler in a thin even layer
- 2 If a thick coat is necessary apply several thin layers
- 3 Allow to dry
- 4 Lightly sand before painting

*For detailed usage instructions, please refer to the Technical Data Sheet

TECHNICAL DATA

Dilution	With a small quantity of water if required
Coverage	0.5 -1.5 kg/m2 depending on substrate conditions
Layer Thickness	1-4mm
Specific Gravity	1.75 +/- 0.05
Colour	White
Standard Compliance	ASTM C- 475
Packaging	5kg and 25kg containers
Storage	12 months in original unopened containers



www.terraco.com

SWEDEN • UK • IRELAND • RUSSIA • TURKEY • ALGERIA • EGYPT
SOUTH AFRICA • JORDAN • UAE • THAILAND • VIETNAM • CHINA • KOREA