

Complete Fire Protection Ltd

Manufacturers of Intumescent Products

FIREPLUG FPG - INTUMESCENT BLOCK GRILLS

INTUMESCENT BLOCK GRILLS HEAVY DUTY

Introduction

Fireplug FPG Intumescent Grills are made to order so can be supplied in any size.

Fireplug FP louvered face plates are made in 50mm increments ranging from 100mmx100mm and are nominally 30mm larger in both height and width than the FPG intumescent grill to allow for surface mounting. Standard colour is white other colours and stainless steel are available.

Fireplug FP: Free air flow is calculated at 65%.

Firelug FPG: Free air flow has been calculated to give a minimum of 50% for a 100 x 100mm - Rising to 76% and higher for a 300 x 300mm and upwards.

Action

Under the action of heat, the openings seal up to prevent the passage of hot gases and toxic fumes.

Installation

Fireplug FPG are designed to suit most fire doors. Simply cut a hole in the door to give a tight fit around the FPG, a bead of intumescent mastic can be placed around the perimeter of the FPG, between the grill and timber, to seal the surrounds if required. Fireplug FP can now be surface mounted each side of Fireplug FPG.



Application:

- Ventilation Duct Work
- Fire Doors
- Access Panels



Also Available
Steel Louvered Face Plates

Visit Our Online Shop: www.cfpltd-shop.co.uk



Intumescent Fire Seals Association



Unit 2 Ferry Steps Industrial Estate, Albert Road, St Philips, Bristol BS2 0XW

Tel: 0117 9711917 Fax: 0117 9711727 Email: mail@cfpltd.co.uk Web Site www.cfpltd.co.uk Online Shop www.cfpltd-shop.co.uk