



## KEIM TURADO

---

KEIM Turado is a fibre reinforced renovation render for application onto both exterior and interior surfaces. It is easy to use and optimised for quick and efficient application.

KEIM Turado offers the highest resistance against cracking because of large, long fibre reinforcement. Due to its outstanding stability, KEIM Turado can be applied in layers as thin as 3mm and its exceptional adhesion means it can be applied onto a wide range of substrates.

KEIM Turado is available in a smooth finish.

# KEIM TURADO

## TECHNICAL INFORMATION

### 1 Field of application

KEIM Turado is a universal, fibre-reinforced, natural white renovation render for interior and exterior use.

KEIM Turado is very versatile and can be applied to sound, mineral substrates and existing renders of mortar group CS II, CS III and CS IV, synthetic resin bound coatings and renders in interior and exterior spaces.

KEIM Turado is very well suited to coat and equalise sound existing renders or coatings and as adhesive mortar on smooth concrete surfaces.

### 2 Product properties

White cement mortar with light aggregates and fibre reinforcement.

Grain size: 0 - 1.0mm

Water absorption: W1

Compressive Strength 4N/mm<sup>2</sup>

Mortar Category CS II

### 3 Application instructions

#### Substrate preparation

All loose, flaking and unstable material must be identified and then thoroughly removed, all surfaces must be thoroughly washed down with clean cold water to remove all surface dirt and dust.

#### Application

Apply to surfaces in layers from 3mm minimum to 12mm maximum. For subsequent applications do not scratch up between coats. Maximum thickness should not exceed 24mm.

KEIM Glassfibre Reinforcing Mesh may be incorporated, if required, by pressing into newly applied KEIM Turado between coats.

Finish off using a float appropriate to the required surface finish (i.e. sponge faced float such as KEIM Hydro Sponge Float).

#### Cleaning of tools

Clean immediately after use with water

#### Setting Time

1 day per 1 mm render layer thickness.

#### Subsequent Finishing

KEIM Turado is suitable for decoration with all exterior and interior KEIM Mineral Paint systems after a minimum period of 1 mm per day (10 day minimum).

#### Consumption

1.35kg per square metre per mm thickness.

Please note that these consumption rates are offered for guideline purposes only and should more accurate measures be required then site trials must be conducted.

#### Packaging

25 kg sacks