



# Weights, water contents & n-coefficients

Model	Weight (kg)	Water Content (l)	n-Coefficient	
TUB1	9.30	3.5	1.231	
TUB2	13.00	5.0	1.251	
TUB3	16.20	6.7	1.253	

# General specification



## CERTIFICATION

Manufactured and tested to EN 442. Carries the CE Mark. Produced under a quality management system - ISO 9001:2015, environmental management system - ISO 14001:2015 and Occupational health and safety management system - OHSAS 18001.



#### **GUARANTEE**

10 year guarantee from date of purchase against manufacturing defects.



## COLOUR

Finished in chrome.



#### MATERIAL

Manufactured from steel.



## ACCESSORIES

Please see page 139.



#### SYSTEM

2 pipe pumped indirect domestic and commercial heating applications.



## CONNECTIONS

 $2 \times \frac{1}{2}$ " BSP as standard.



## AIR VENTS

Included in the packaging.



#### OPERATING PRESSURES

Tested to a pressure of 9.6 bar. Working pressure of up to 7.4 bar.



#### DUAL FUEL

ECO450 dual fuel heater kit available. Please see page 138.



# DELIVERY

2 - 5 working days.



# VALVES

Please see page 138.

For more general information, please see page 260.

# Technical information & heat outputs

Order Code	Nominal Height (H) (mm)	Nominal Length (L) (mm)	Heat Outputs @ ∆T 50°C		Heat Outputs @ ∆T 30°C		Dual Fuel Rating	
		()	()	Watts	Btu/h	Watts	Btu/h	Watts
	TUB1	770	600	318	1085	170	580	450
	TUB2	1130	600	448	1529	236	805	450
	TUB3	1400	600	547	1866	288	983	450