



Dimensions

Standard/Straight Bodies

15mm Standard









Model	G	В	L	Н*	h*
Modet	(in)	in) (mm) (mm) (mm)	(mm)	(mm)	
15mm Standard	1/2	64.0	32.0	108.0	72.0
15mm or ½" BSP Straight	1/2	95.0	33.0	113.0	77.0
22mm or ¾" BSP Straight	3/4	106.0	37.0	116.0	80.0

Horizontal/Vertical Angle Bodies

15mm or 1/2" **BSP Horizontal**





15mm or $\frac{1}{2}$ "/22mm or

Model	G	В	L	Н*	h*
Modet	(in)	(mm)	(mm)	(mm)	(mm)
15mm or ½" BSP Horizontal	1/2	53.0	37.0	115.0	79.0
15mm or ½" BSP Vertical	1/2	58.0	26.0	109.0	75.0
22mm or ¾" BSP Vertical	3/4	66.0	29.0	111.0	87.0

H* Fitted with 2TRVHEAD or 2TRVRSHEAD h* Fitted with 2TRVADJHEAD

NB: All measurements are nominal.

TRV head not included.

General specification



CERTIFICATION

Produced under a quality management system -ISO 9001:2008 and complies to EN 215-1.



GUARANTEE

2 year guarantee from date of purchase against manufacturing defects.



COLOUR

Finished in nickel or chrome plate.



CONNECTIONS

Compression or pushfit.



OPERATING PRESSURES

Tested to a maximum pressure of 10 bar.



OPERATING **TEMPERATURE**



Maximum 120°C.



DELIVERY

2 - 5 working days.

For more general information, please see page 260.



TRV bodies

Description	Metal Finish	Order Code	Minimum Order Qty
15mm or ½" BSP Vertical Angle	Nickel	2TRV15AN	1
15mm or ½" BSP Horizontal Angle	Nickel	2TRV15IN	1
15mm or ½" BSP Straight	Nickel	2TRV15SN	1
15mm Standard TRV 2-WAY Body	Chrome	2TRVB0C	1
15mm Standard TRV 2-WAY Body	Nickel	2TRVBON	1
22mm or ¾" BSP Vertical Angle (one way flow)	Nickel	2TRV22AN	1
22mm or ¾" BSP Straight (one way flow)	Nickel	2TRV22SN	1
M28 TRV Bodu	Nickel	2TRVADAP	1

Accessories

Standard TRV Head Only	-	2TRVHEAD	1
PETITE TRV Head Only	-	PETTRVHEAD	1
Standard TRV Head 'Contract' Only	-	2TRVHEADCON	1
Theft Resistant Ring	-	2TRVRING	1
Theft Resistant Collar	-	2TRVCOLLAR	1
Commissioning Cap	-	2TRVCAP	1
Impaired Dexterity TRV Head Only	-	2TRVHEADDEX	1