

The PETITE combines attractive design with total reliability, it also incorporates our 2-way flow technology. The PETITE is available as a single valve or a convenient 'TRV & manual' valve pack (see page 242), in either 10mm or 15mm sizes and finished in a bright nickel. Available in straight and angle versions.



General specification



CERTIFICATION

Produced under a quality management system -ISO 9001:2008 and complies to EN 215.



GUARANTEE

2 year guarantee from date of purchase against manufacturing defects.



COLOUR

Finished in nickel.



CONNECTIONS

Compression or pushfit.



OPERATING PRESSURES

Tested to a maximum pressure of 10 bar (compression), 3 bar (pushfit).



OPERATING TEMPERATURE

Maximum 120°C (compression), 92°C (pushfit).




DELIVERY


2 - 5 working days.

For more general information, please see page 260.






10/15mm Angle



15mm Straight

Model	Α	В	С	D	E
Modet	(mm)	(mm)	(mm)	(mm)	(mm)
10mm Angle	89.0	33.0	61.0	34.0	60.0
15mm Angle	89.0	33.0	61.0	34.0	60.0
15mm Straight	93.0	40.0	67.0	-	-

PETITE Pushfit



Model	Α	В	С	D		
Modet	(mm)	(mm)	(mm)	(mm)		
10mm Angle	89.0	33.0	61.0	30.0		
15mm Angle	89.0	39.0	61.0	36.0		
Model	Е	F	G	Н		
Model	E (mm)	F (mm)	G (mm)	H (mm)		

34.0

56.0

15mm Angle

NB: All measurements are nominal.

61.0

60.0



PETITE

Description	Metal Finish	Order Code	Minimum Order Qty
10mm PETITE TRV Angle	Nickel	PETTRV10N	10
15mm PETITE TRV Angle	Nickel	PETTRV15N	10
15mm PETITE TRV Straight	Nickel	PETTRV15NS	10

PETITE pushfit



10mm PETITE (90° Pushfit Elbow) Angle	Nickel	PETTRV10NPF90	10
15mm PETITE (90° Pushfit Elbow) Angle	Nickel	PETTRV15NPF90	10