

# JOINT SKIM & FILL

QUICK DRY

## FILLER FOR SURFACE FINISHING, FILLING & PLASTERBOARD JOINTING

- ◆ ONE COAT
- ◆ EASY TO SAND
- ◆ NO SHRINKAGE, NO DEPTH LIMIT
- ◆ NO NEED TO SPOT PRIME



### PURPOSE

For plasterboard jointing, filling and surface finishing.  
Ready to paint in 3 hours perfect for completing the job in one day.

### SUBSTRATES

Joint, Skim & Fill Quick Dry can be applied to:  
- Gypsum, plaster board, old painted surfaces, cement, concrete, cellular concrete and primed wood.

### OVERCOATING

Joint, Skim & Fill Quick dry can be coated with any type of filler, paint or wall coating.

### Physical and technical FEATURES

- Joint Skim & Fill Quick Dry: adhesive and filler, in powder form made of quarry extracts and cellulosic binder.
- Characterization (NFT 36-005): Family III class 3.
- Codification (NFT 30-608): G<sub>3</sub>E<sub>5</sub>S<sub>1</sub>V<sub>0</sub>W<sub>0</sub>A<sub>0</sub>C<sub>0</sub>.
- Mixing rate:  
Filling: add 380ml water per 1kg powder (38%).  
Skimming: add 450ml water per 1kg powder (45%).
- Application thickness: no depth limit.
- Coverage: 1.1kg covers 1m<sup>2</sup> at 1mm depth.
- Working time: 40 minutes.
- Setting time: second coat 45 mins.
- Overcoating: can be painted in 3 hours average time (after complete drying).
- Color: white.
- Adhesion: filler/substrate (NFT 30-608): > 0,5 MPa.

### USE AND STORAGE CONDITIONS

- Application tools: filling knife, trowel or blade.
- Tool cleaning: after use, product residue can be rubbed off tools when dry (water cleaning is not necessary).
- Preservation: guaranteed for 12 months from purchase when used as intended, kept in its original sealed packaging and stored away from humidity. If found to be faulty within the guarantee period, we will arrange a replacement on proof of purchase.

### PACKAGING

- Bags: 5kg and 10kg.

### RECOMMENDATIONS and care for use

The times mentioned are indicative and depend on the substrate, coat thickness, and the ambient conditions.  
Do not apply at a temperature below 8°C or above 35°C nor at a relative humidity over 70%.

### SUBSTRATES PREPARATION

Substrates to be prepared as per the current trade practices.  
Substrates must be hard, cohesive, clean, sound and dry.

### NORMATIVE DOCUMENTS to be referred to

- BS EN 13279-1:2008 (Gypsum binders and gypsum plasters)
- NFT 30-608: Coating fillers for interior works and/or exterior.
- NFT 36-005: Characterization of paint products.
- DTU 59.1 (NFP 74-201): Building paint works.
- DTU 59.4 (NFP 74-204): Wall papers and wall coating works.
- French DTU 25.31 (NF P72-202-2).
- BS EN 13963 : 2014 - Jointing materials for gypsum boards.

### HEALTH AND SAFETY

It is recommended to wear gloves and glasses while applying Joint Skim & Fill Quick Dry. Always wear a dust mask when sanding.

Dispose of unused product and packaging responsibly at your local waste collection centre.

Safety data sheet available at [www.toupret.co.uk](http://www.toupret.co.uk).

The data sheet information, especially the guidelines relevant to the application and final use of the product are provided in good faith and result from TOUPRET's experience and knowledge of the products. The product should be used as per the trade practices rules book and in reference to our recommendations. The information provided is relevant to applications processed at a temperature of 20°C, a relative humidity of 50% and on average absorbency substrates. The times mentioned are only indicative and depend on the substrate, the coat thickness, and the ambient conditions.



\* Information on the emission level of volatile substances into indoor air, presenting a risk of toxicity by inhalation, on a scale from A+ (very low emissions) to C (high emissions).