

# JOINT & SKIM

READY TO USE

## FILLER FOR SURFACE FINISHING & PLASTERBOARD JOINTING

- ◆ EASY TO SAND
- ◆ SMOOTH APPLICATION
- ◆ NO NEED TO SPOT PRIME
- ◆ FOR MANUAL OR SPRAY APPLICATION



### PURPOSE

Ready to use interior filler for plasterboard jointing and surface finishing. Suitable for manual and machine application with Airspray machines.

### SUBSTRATES

Joint & Skim Ready To Use can be applied to:  
- Gypsum, plaster board, old painted surfaces, cement, concrete, cellular concrete and primed wood.

### OVERCOATING

Joint & Skim Ready To Use can be coated with any type of filler, paint or wall coating.

### Physical and technical FEATURES

- Joint & Skim Ready To Use: filler in ready mixed form for interior use, made of mineral components and synthetic resin.
- Characterization (NFT 36-005): Family III - Class 2.
- Codification (EN 16566):  $G_3S_1V_0W_0A_0C_0R_0$ .
- Mixing rate: ready to use.
- Application thickness: up to 5mm.
- Coverage: 1.7kg covers 1m<sup>2</sup> at 1mm depth.
- Working time: unlimited.
- Setting time: second coat as soon as the filler is hard and dry to the touch.
- Overcoating: can be painted in 12 to 24 hours average time (after complete drying).
- Color: white.
- Adhesion: filler/substrate (EN 16566): > 0.5 Mpa.

### USE AND STORAGE CONDITIONS

- Application tools: filling knife, trowel or blade.
- Tool cleaning: after use, product residue can be rubbed off tools when dry (water cleaning is not necessary).
- Preservation: product guaranteed 12 months.  
Stored away from sunlight and frost. If found to be faulty within the guarantee period, we will arrange a replacement on proof of purchase.

### PACKAGING

- Buckets: 10kg and 20kg.

### RECOMMENDATIONS and care for use

The times mentioned are indicative and depend on the substrate, coat thickness, and the ambient conditions. Do not apply at a temperature below 8°C or above 35°C nor at a relative humidity over 70%.

### SUBSTRATES PREPARATION

Substrates to be prepared as per the current trade practices. Substrates must be hard, cohesive, clean, sound and dry.

### NORMATIVE DOCUMENTS to be referred to

- BS EN 13279-1:2008 (Gypsum binders and gypsum plasters)
- EN 16566: Coating Fillers for interior and/or exterior works.
- NFT 36-005: Characterization of paint products.
- DTU 59.1 (NFP 74-201): Building paint works.
- DTU 25.41 (NFP 72-203-1) Building works - Gypsum plasterboard works.
- BS EN 13963 : 2014 - Jointing materials for gypsum boards.

### HEALTH AND SAFETY

It is recommended to wear gloves and glasses while applying Joint & Skim Ready To Use.

Always wear a dust mask when sanding.

Dispose of unused product and packaging responsibly at your local waste collection centre.

Safety data sheet available at [www.toupret.co.uk](http://www.toupret.co.uk).

The data sheet information, especially the guidelines relevant to the application and final use of the product are provided in good faith and result from TOUPRET's experience and knowledge of the products. The product should be used as per the trade practices rules book and in reference to our recommendations. The information provided is relevant to applications processed at a temperature of 20°C, a relative humidity of 50% and on average absorbency substrates. The times mentioned are only indicative and depend on the substrate, the coat thickness, and the ambient conditions.



\* Information on the emission level of volatile substances into indoor air, presenting a risk of toxicity by inhalation, on a scale from A+ (very low emissions) to C (high emissions).