

# PLASTER OF PARIS

## SHAPING & MOULDING

- ◆ EASY TO SHAPE & MOULD
- ◆ QUICK SETTING
- ◆ EXTRA FINE
- ◆ EASY TO SAND



### PURPOSE

Ideal for interior decorative shaping and moulding and excellent for fine finishing.  
Bright white.

### SUBSTRATES

Plaster Of Paris can be applied to unpainted, new or renovated, substrates:  
- Gypsum plaster, gypsum tile, plasterboards/drywall lining  
- Cement, concrete, breeze blocks, bricks, mortar.

### OVERCOATING

Plaster Of Paris can be overcoated with any type of filler, paint or wall coating.

### Physical and technical FEATURES

- Mixing rate: add 750ml water per 1kg powder (75%).
- Application thickness: no depth limit.
- Capacity: 1kg fills 1.2L when mixed.
- Working time: 10 to 15 minutes.
- Overcoating: can be painted in 24 to 72 hours average time (after complete drying).
- Color: extra white.

### USE AND STORAGE CONDITIONS

- Application tools: filling knife, trowel or blade.
- Tool cleaning: after use, product residue can be rubbed off tools when dry (water cleaning is not necessary).
- Preservation: guaranteed for 12 months from purchase when used as intended, kept in its original sealed packaging and stored away from humidity.  
If found to be faulty within the guarantee period, we will arrange a replacement on proof of purchase.

### PACKAGING

Bag: 4kg.

### RECOMMENDATIONS and care for use

The times mentioned are indicative and depend on the substrate, coat thickness, and the ambient conditions.

Do not apply at a temperature below 8°C or above 35°C nor at a relative humidity over 70%.

Moisten the substrate before application.

Do not apply cement based products on the plaster.

Stop using the mixture as soon as it starts to harden.

### SUBSTRATES PREPARATION

Substrates to be prepared as per the current trade practices.  
Substrates must be hard, cohesive, clean, sound and dry.

### NORMATIVE DOCUMENTS to be referred to

- BS EN 13279-1:2008 (Gypsum binders and gypsum plasters).
- BS EN 13279-1:2005 - Jointing materials for gypsum boards.

### HEALTH AND SAFETY

It is recommended to wear gloves and glasses while applying Plaster Of Paris.

Always wear a dust mask when sanding.

Dispose of unused product and packaging responsibly at your local waste collection centre.

Safety data sheet available at [www.toupret.co.uk](http://www.toupret.co.uk)

The data sheet information, especially the guidelines relevant to the application and final use of the product are provided in good faith and result from TOUPRET's experience and knowledge of the products. The product should be used as per the trade practices rules book and in reference to our recommendations. The information provided is relevant to applications processed at a temperature of 20°C, a relative humidity of 50% and on average absorbency substrates. The times mentioned are only indicative and depend on the substrate, the coat thickness, and the ambient conditions.



\* Information on the emission level of volatile substances into indoor air, presenting a risk of toxicity by inhalation, on a scale from A+ (very low emissions) to C (high emissions).