

RENOVATION SKIMCOAT

DECORATORS SKIMCOAT

READY TO USE FILLER FOR LEVELLING & FINISHING DAMAGED AND TEXTURED SURFACES

- ◆ IDEAL FOR COVERING TEXTURED AND ROUGH SURFACES
- ◆ CERTIFIED FOR PLASTERBOARD JOINTING
- ◆ NO PVA REQUIRED, NO NEED TO SPOT PRIME
- ◆ EASY TO SAND



PURPOSE

Ready to use interior filler for surface levelling, skimming and jointing.

Especially suitable for high-build applications (up to 5mm) such as levelling rough surfaces and covering texture.

SUBSTRATES

Renovation Skimcoat can be applied to either new or renovated substrates, unpainted or painted:

- Gypsum plaster, plasterboards/drywall lining
- Old painted surfaces, cement, concrete, cellular concrete
- Old textured surfaces, breeze blocks, bricks, and stone.

OVERCOATING

Renovation Skimcoat can be overcoated with any type of filler, paint or wall coating.

Physical and technical FEATURES

- Renovation Skimcoat: interior filler in ready mixed form, made of selected mineral extracts and resin.
- Characterization (NFT 36-005): Family III - class 2.
- Codification (EN 16-566): $G_3S_2V_0W_0A_0C_0R_0$.
- Mixing rate: ready to use.
- Application thickness: 5mm.
- Capacity: 1.7kg covers 1m² at 1mm thick.
- Setting time: second coat as soon as the filler is hard and dry to the touch.
- Overcoating: can be painted in 12 to 24 hours average time (after complete drying).
- Color: white.
- Adhesion: filler/substrate (EN 16-566): > 0.5 Mpa.

USE AND STORAGE CONDITIONS

- Application tools: filling knife, trowel or blade.
- Tool cleaning: after use, product residue can be rubbed off tools when dry (water cleaning is not necessary).
- Preservation: guaranteed for 12 months from purchase when used as intended, kept in its original sealed packaging and stored away from sunlight and frost.

If found to be faulty within the guarantee period, we will arrange a replacement on proof of purchase.

PACKAGING

Bucket: 10kg.

RECOMMENDATIONS and care for use

The times mentioned are indicative and depend on the substrate, coat thickness, and the ambient conditions.

Do not apply at a temperature below 8°C or above 35°C nor at a relative humidity over 70%.

SUBSTRATES PREPARATION

Substrates to be prepared as per the current trade practices. Substrates must be hard, cohesive, clean, sound and dry.

NORMATIVE DOCUMENTS to be referred to

- BS EN 16566:2014 (Paints and varnishes. Fillers for internal and/or external works).
- NF Environment – Paint fillers (NF446).
- BS EN 13963 : 2014 - Jointing materials for gypsum boards.

HEALTH AND SAFETY

It is recommended to wear gloves and glasses while applying Renovation Skimcoat. Always wear a dust mask when sanding. Dispose of unused product and packaging responsibly at your local waste collection centre.

Preservatives: Contains 1,2-benzisothiazolin-3-one; C(M)IT / MIT (3:1); MBIT. May produce an allergic reaction. Safety data sheet available at www.toupret.co.uk

The data sheet information, especially the guidelines relevant to the application and final use of the product are provided in good faith and result from TOUPRET's experience and knowledge of the products. The product should be used as per the trade practices rules book and in reference to our recommendations. The information provided is relevant to applications processed at a temperature of 20°C, a relative humidity of 50% and on average absorbency substrates. The times mentioned are only indicative and depend on the substrate, the coat thickness, and the ambient conditions.



* Information on the emission level of volatile substances into indoor air, presenting a risk of toxicity by inhalation, on a scale from A+ (very low emissions) to C (high emissions).