

SKIM-FLEX

TX 140

FLEXIBLE SKIMCOAT FOR MOVING & TILED SUBSTRATES

- ◆ EXCEPTIONAL ADHESION, EVEN ON TILES
- ◆ IDEAL FOR KITCHENS AND BATHROOMS
- ◆ EASY TO SPREAD & SAND
- ◆ REMAINS FLEXIBLE WHEN DRY



PURPOSE

Ready to use flexible skimcoat filler.

For covering and levelling all types of substrates, inside and out, including soft and moving substrates and great for covering tiles. For filling up to 5mm and fine surface covering.

SUBSTRATES

Skim-Flex can be applied to all painted and unpainted substrates:

- Tiles, ceramics, glass, polystyrene, cork, cellula, cement
- Gypsum plaster, plasterboards/drywall lining, cellular concrete
- Old painted surfaces, all conventional surface preparation filler.

OVERCOATING

Skim-Flex may be overcoated by all types of indoor and outdoor paint (except mineral paint) and wall coverings (check with us).

Physical and technical FEATURES

- Skim-Flex: interior/exterior filler in ready mixed form, made from calcium carbonate and selected resins.
- Characterization (NFT 36-005): Family IV-4b.
- Codification (EN 16-566): $G_3S_2V_1W_2A_0C_0R_0$.
- Mixing rate: ready to use.
- Application thickness: 5mm.
- Capacity: 1.6kg covers 1m² at 1mm depth.
- Setting time: second coat as soon as the filler is hard and dry to the touch.
- Overcoating: can be painted in 24 to 48 hours average time (after complete drying).
- Color: white.
- Adhesion: filler/substrate (EN 16-566): > 0.8 Mpa.

USE AND STORAGE CONDITIONS

- Application tools: filling knife, trowel or blade.
- Tool cleaning: after use, product residue can be rubbed off tools when dry (water cleaning is not necessary).
- Preservation: guaranteed for 12 months from purchase when used as intended, kept in its original sealed packaging and stored away from sunlight and frost.

If found to be faulty within the guarantee period, we will arrange a replacement on proof of purchase.

PACKAGING

Tub: 5kg.

RECOMMENDATIONS and care for use

The times mentioned are indicative and depend on the substrate, coat thickness, and the ambient conditions. Do not apply at a temperature below 5°C or above 35°C nor at a relative humidity over 80%.

SUBSTRATES PREPARATION

Substrates to be prepared as per the current trade practices. Substrates must be hard, cohesive, clean, sound and dry.

NORMATIVE DOCUMENTS to be referred to

- BS EN 16566:2014 (Paints and varnishes. Fillers for internal and/or external works).

HEALTH AND SAFETY

It is recommended to wear gloves and glasses while applying Skim-Flex. Always wear a dust mask when sanding.

Dispose of unused product and packaging responsibly at your local waste collection centre.

Preservatives: Contains 1,2-benzisothiazolin-3-one; C(M)IT / MIT (3:1); MBIT. May produce an allergic reaction.

Safety data sheet available at www.toupret.co.uk

The data sheet information, especially the guidelines relevant to the application and final use of the product are provided in good faith and result from TOUPRET's experience and knowledge of the products. The product should be used as per the trade practices rules book and in reference to our recommendations. The information provided is relevant to applications processed at a temperature of 20°C, a relative humidity of 50% and on average absorbency substrates. The times mentioned are only indicative and depend on the substrate, the coat thickness, and the ambient conditions.