peak collection



Care and maintenance guide

eurocell

MAINTENANCE INSTRUCTIONS

Cylinder locks

Lubricate 6 monthly using an oil based lubricant.
Do not use graphite powder or WD40.

1. Apply 4 drops on each side of the key
2. Place the key in the lock & move back & forth 10 – 15 times to lubricate the cylinder
3. Repeat at least once a year, or when necessary



Multipoint locks

- Wipe the door lock and keeps down with a clean damp cloth to remove dirt/grit
- Do not use household chemical cleaners or abrasive cleaners
- Do not use any cleaners which may affect the corrosion resistance of the product
- Avoid acid or ammonia-based cleaners & wipe dry after cleaning
- Twice per year apply petroleum jelly to all “contact” areas of Lock & Keeps as shown (Grease Points)
- Periodically inspect all fixings are secure. Any loose fixings should be tightened by a suitably qualified person



Always lift the handle on a composite door to ensure all locking points are fully engaged, this ensures maximum security, keeps the door correctly aligned, and prevents issues like warping or premature wear, helping your door perform reliably and last longer.

Door furniture

For continued protection of the quality finish and appearance of all Fab & Fix hardware (letterplates, Handles, Knockers & Hinges) routine cleaning must be carried out, wash the hardware with a very mild soapy water and a cloth – making sure to dry well afterwards.

Moving parts should also be lightly lubricated using 3 in 1 oil at least twice a year. This procedure is particularly essential if products are installed within a 25-mile radius of coastal areas or close proximity to a building site or large industrial area, where more frequent cleaning may be required to prevent the accumulation of corrosive contaminants.

Door faces & frame

Using only soapy water and a sponge, wipe down the faces of the door and frame and immediately dry them using a towel, this should be repeated every month.





eurocell.co.uk

MADE & RECYCLED IN THE UK

eurocell

Product specification is subject to change without notification. Please also note that colours shown are illustrative only, as the printing process does not allow 100% accurate colours to be reproduced.

PEAKCARE | Is1/Feb26