

Fast Drying 6

ICB STRATAPRIME is a priming solution designed to deeply penetrate and seal porous surfaces to provide a base for bituminous waterproofing and flashing systems. Ideal for the sealing of metal, concrete, cement, slate, roofing fibre cement, bitumen based materials and flashing tapes. It contains a wetting agent to enable it to be applied to 'damp' as well as dry surfaces.

Benefits:

- Provides a base for bituminous waterproofing and flashing systems
- Ideal for the sealing of metal, concrete, cement, slate, roofing fibre cement, bitumen based materials and flashing tapes
- Contains a wetting agent to enable it to be applied to 'damp' as well as dry surfaces

Technical Data

	ICB STRATAPRIME	
COLOUR	Black	
SPECIFIC GRAVITY	0.88 @ 15°C	
DRYING TIME	Touch dry 30 mins, fully dry 1.5 hours	
PACKAGING	5 and 25 litre Drums	
FLASH POINT	38 °C	
COVERAGE	Metal Surfaces	12-16m²/L
	Porous Surfaces	6-8 m²/L
	Lightweight concrete screeds /asbestos cement	3.5 -5 m²/L
SHELF LIFE	24 months in tightly sealed undamaged containers	
SOLIDS CONTENT	40% by weight minimum	



ICB (Waterproofing) Ltd
Units 9-11 Fleets Industrial Estate,
Willis Way,
Poole,
BH15 3SU

Tel: 01202 785200
Fax: 01202 785201

Email: info@icb.uk.com

Instructions for use:

- Apply to clean, dry, and sound surfaces. For best results, surfaces should be free of dust, oil, and other contaminants.
- ICB STRATAPRIME is resistant to rainfall and atmospheric pollution.
- ICB STRATAPRIME is a flammable solvent and all normal precautions against fire must be taken during both storage and use. Keep away from sources of ignition.