



SAFETY AT THE HIGHEST LEVEL

Ladder Stand off.

Assembly Instructions



Easi-Dec Access Systems Ltd.,
Merlin House,
Blaydon Road,
Sandy
SG19 1RZ
Tel: +44 (0) 1767 691812
Fax: +44 (0) 1767 691802

E-Mail: info@easi-dec.com
Internet: www.easi-dec.com

PLEASE BE ADVISED: Before assembling the Ladder Stand off for the first time, it is highly recommended that Installers familiarise themselves with the component parts and carry out a test assembly and disassembly in a safe area away from the point of final installation. All component parts detailed in the operating instructions must be used in the assembly of the system. Should a piece be missing or appear defective do not continue to assemble and contact Easi-Dec Immediately.

Step 1



Ladder stand-off ready for attaching to the Ladder.

Step 2



Position the ladder stand-off over the top end of the ladder ensuring the hooks are pushed firmly over the rungs.

Step 3



Pull the sprung hook over the second rung ensuring it's firmly fixed into position. **WARNING!** It is very important this sprung hook is fixed into position before use, as it prevents the Ladder stand-off sliding off the top end of the Ladder.

Step 4



FIG 1. Access Corners

Position the Ladder against the wall or to access corners **FIG 1.**

Step 5



Use Ladder spurs supplied by Easi-Dec to aid stability and prevent outward slip.

Remember

- Work carefully – Never rush.
- Always fit the sprung hook.
- Do not use in adverse weather conditions.
- Always erect using the 4:1 rule.

Dismantle: Reverse the above procedure.