

571.EL Electromechanical Exit Device (Electric Latch Retraction)

A complete range of CE Marked Exit Hardware w. Electronic Motorised Control

The Briton 571.EL may be used as a single rim latch or in conjunction with the standard Briton 570 Series Pullman latch kits to create multi-point latching for single or double door combinations.



• Suitable for doors 600mm to 1200mm wide (for doors to 840mm - see 571.2.EL)*

One Point Locking (571.1)

- Suitable for single doors and the first opening leaf of rebated double door applications
- Non-handed will suit both left and right handed doors
- Upgrade available to multi-point latching
- Optional models include alarmed and manually dogged (hold-open) functions
- Compatible with all access control systems
- Power supply 24Vdc w. Battery Back-Up**
- Connecting cable @ 4000mm
- Degree of protection IP20
- Operating temperature -10°C to + 50°C
- Timed latch withdrawal from 3 to 30 seconds
- Electronic dogging (hold-back)
- Protective anti-bacterial coating

* The touch bar and chassis (571.1 & 571.2) can be cut down on site for accurate sizing ** It is essential that batteries are used, in case of power failure during a motorized operation of the device



Compatible Outside Access Devices (OAD) -

1413/LE.SE or 1413/KE.SE





Compatible Power Supply w. Battery Back-up PS06 - 24Vdc 2.0 Amp Power Supply/Field Relay (PSU)

Briton 570 Series Exit Hardware

Briton 570 panic exit devices have been designed to offer modular solutions for mid to high end specification, providing a combination of style, safety and optimum security. Comprising a one-point locking touch bar device and optional modular locking elements, these units offer increased flexibility and adaptability to suit individual requirements.