

## OBEXION MD XR DOS SECURITY SHUTTER



### ACCREDITATIONS

- Independently tested to international security standard FE/BR
- Approved for use on USA Government Interests Abroad by US Department of State (DoS)
- Certified to SD-STD-01.01 Rev. G (Amended)



### CERTIFIED PROTECTION AGAINST:



#### **Forced Entry: Bodily Force**

Mitigation of opportunist intruder attempts using manual or bodily force including tools.



#### **Mob Attack**

Mitigation of forced entry through means of overpowering security measures in mob situations.

The Obexion MD XR DoS shutter has been successfully been tested and gained approved for use by the US Department of State (DOS), making it the first ever security shutter to do so.

Accredited to the FE/BR (Forced Entry/Ballistic Resistance) standard, DoS certification provides the Obexion MD XR DoS with approval for use on US official property. This includes Government Buildings, US Government interests abroad, and other high risk applications. Featuring unique LockDown technology,

The first point of entry security measure has been certified to the FE part of the SD-STD-01.01 Rev G (Amended) standard. Designed to prolong a mob attack, the test simulated a 5 minute attack from a two-man team and a 15-minute attack from a six-man team.

## OBEXION MD XR DOS SECURITY SHUTTER

### Provisions of SD-STD-01.01 Rev. G

SD-STD-01.01 Rev G (Amended) is the Forced Entry standard offering certification as mitigation of mob attacks consisting of both 5 and 15 minute intervals. The program establishes standards for forced entry levels of protection as a function of

#### SUITABLE APPLICATIONS INCLUDE:

- Approved for US Foreign Interests Abroad
- Defence Estate
- Military and International Security

#### SHUTTER CURTAIN

Extruded aluminium LockDown profiles.  
Finish as delivered: polyester powder coated in standard RAL/BS colour.

#### BOTTOM RAIL

Reinforced extruded aluminium section with strengthened core.

#### CONTROLS

Full range of compatible controls including push button switch, key switch, radio control or integration into existing building management systems and third party alarm.  
Safety on close as assessment directs.

#### PRODUCT REFERENCE

Obexion MD XR DoS Security Shutter

#### PERFORMANCE

Certified to SD-STD-01.01 Rev. G (Amended) for 5-Minute FE & 15-Minute FE

#### SUITABLE SUBSTRATES:

Certified installation onto:

- Reinforced Concrete
- Structural Steelwork

#### FRAMES/GUIDES

Heavy duty guide profiles anchored direct to the structure.

Finish as delivered: polyester powder coated in standard RAL/BS colour.

#### OPERATION

Motorised to allow controlled ascent and descent.  
240v - Low duty cycle or where limited to single phase supply.

415v - High duty cycle or for larger apertures.

Option to be connected to building management & access control systems.

