

OBEXION MD SR4 SECURITY SHUTTER

ACCREDITATIONS

- Independently tested by the Loss Prevention Certification Board (LPCB)
- Certified to LPS 1175 Issue 7: SR4
- Secured by Design Police Preferred Specifications



CERTIFIED PROTECTION AGAINST:



Forced Entry:
Bodily Force

Mitigation of opportunist intruder attempts using manual or bodily force including tools.



Forced Entry:
Power Tools

Protecting against deliberate forced entry of premises using mechanically-enhanced power tools.



Bespoke

Securing people, property and assets against bespoke risks and severe threats.

Designed for medium risk commercial applications, the Obexion MD SR4 shutter resists a sustained and experienced attempt at forced entry using an extended range of hand and power tools.

Incorporating the LockDown technology, the Obexion MD SR4 requires no auxiliary locking to maintain the security rating. This ensures the shutter is never left in an insecure position, facilitating operation of the shutter as a first point of entry.

LOCKDOWN TECHNOLOGY

No auxiliary locking required, manual or electronic.

Unique profiles lock shutter in any stop position - fully closed or otherwise.

Allows external first point-of-entry through the shutter.

OBEXION MD SR4 SECURITY SHUTTER

SUITABLE APPLICATIONS INCLUDE:

- Laboratories and Research buildings
- Critical National Infrastructure
- Cash handling, precious metals and stones storage

APPROVED DIMENSIONS

Internal Face Fit:	External Face Fit:
Minimum certified height: 1.0m	Minimum certified height: 1.8m
Maximum certified height: 10.0m	Maximum certified height: 10.0m
Minimum certified width: 1.0m	Minimum certified width: 1.0m
Maximum certified width: 6.0m	Maximum certified width: 6.0m

SHUTTER CURTAIN

Extruded aluminium LockDown profiles.

BOTTOM RAIL

Finish as delivered: polyester powder coated in standard RAL/BS colour.

CONTROLS

Full range of compatible controls including push button switch, key switch, radio control or integration into existing building management systems and third party alarm.

Safety on close as assessment directs.

OPTIONS

Anti-cut core for protection against Bespoke risks including grinder attack.

PRODUCT REFERENCE

Obexion MD SR4 Security Shutter

PERFORMANCE

Certified to LPS 1175 Issue 7 SR4

SUITABLE SUBSTRATES:

Internal and External installations complete with sub assembly steel frames as required

Certified installation onto:

- Reinforced Blockwork
- Reinforced Concrete
- Structural Steelwork

FRAMES/GUIDES

Heavy duty guide profiles anchored direct to the structure.

Finish as delivered: polyester powder coated in standard RAL/BS colour.

OPERATION

Motorised to allow controlled ascent and descent.
240v - Low duty cycle or where limited to single phase supply.

415v - High duty cycle or for larger apertures.

