

## OBEXION MD SR5 SECURITY SHUTTER

### ACCREDITATIONS

- Independently tested by the Loss Prevention Certification Board (LPCB)
- Certified to LPS 1175 Issue 7: SR5
- Secured by Design Police Preferred Specifications



### CERTIFIED PROTECTION AGAINST:



Forced Entry:  
Bodily Force

Mitigation of opportunist intruder attempts using manual or bodily force including tools.



Forced Entry:  
Power Tools

Protecting against deliberate forced entry of premises using mechanically-enhanced power tools.



Bespoke

Securing people, property and assets against bespoke risks and severe threats.

The security that the Obexion MD SR5 shutter offers is a dramatic increase to that of the Obexion SR4 security shutter. The addition of the 18V Reciprocating saw and 18V power for all the electric tools, requires far greater resistance during the 10-minute attack time than the SR4 security level.

The Obexion MD SR5 shutter range is designed to protect against a sustained and professional means of attempting entry using an extended range of hand and performance power tools.

### LOCKDOWN TECHNOLOGY

No auxiliary locking required, manual or electronic.

Unique profiles lock shutter in any stop position - fully closed or otherwise.

Allows external first point-of-entry through the shutter.

## OBEXION MD SR5 SECURITY SHUTTER

### SUITABLE APPLICATIONS INCLUDE:

- Critical National Infrastructure
- Defence Estate
- Military and National Security

### APPROVED DIMENSIONS (INTERNAL FACE FIT ONLY)

Minimum certified height: 1.0m Minimum certified width: 1.0m

Maximum certified height: 10.0m Maximum certified width: 6.0m

### SHUTTER CURTAIN

Extruded aluminium LockDown profiles.  
Finish as delivered: polyester powder coated in standard RAL/BS colour.

### BOTTOM RAIL

Reinforced extruded aluminium section with strengthened core.  
Finish as delivered: polyester powder coated in standard RAL/BS colour.

### CONTROLS

Full range of compatible controls including push button switch, key switch, radio control or integration into existing building management systems and third party alarm.  
Safety on close as assessment directs.

### OPTIONS

Anti-cut core for protection against Bespoke risks including grinder attack.

### PRODUCT REFERENCE

Obexion MD SR5 Security Shutter

### PERFORMANCE

Certified to LPS 1175 Issue 7 SR5

### SUITABLE SUBSTRATES:

Certified installation onto:

- Reinforced Concrete
- Structural Steelwork

### FRAMES/GUIDES

Heavy duty guide profiles anchored direct to the structure.

Finish as delivered: polyester powder coated in standard RAL/BS colour.

### OPERATION

Motorised to allow controlled ascent and descent.  
240v - Low duty cycle or where limited to single phase supply.

415v - High duty cycle or for larger apertures.

