

# FAAST AUTOMATIC PURGING UNIT

The FAAST Automatic Purging Unit provides a fully integrated and compact solution with user-selectable preventative or event triggered purging programs.

ASD systems continuously monitor the air in a protected environment, potentially subjecting the system to contamination over time. In order to prevent the build-up of pipe or aspiration hole contaminants, regular ASD system purging with compressed air is essential.

In contrast to conventional purging systems, Honeywell's compact and user-friendly AFE70-2 and AFE70-3 units features a single built-in Solenoid valve, which initiates the release of air into the ASD system. This valve also increases reliability by protecting the unit from any compressed air damage and can be accessed through a control board that is integrated into the housing.

Installation time is greatly reduced, thanks to a compact and fully integrated design, removing the need for mechanical and electrical control devices. Further cost savings can be leveraged by a reduced need for cabling and pipe work to commission the system.

With user-definable purging processes and customizable program features, the FAAST Automatic Purging Units deliver continuous and uninterrupted air flow and is also optimized to assist with benchmark preventative maintenance regimes, through automatic purging processes that can be set up at specific times. These purging processes are independent of any fault-initiated purging procedures performed by the system.

Designed with the engineer in mind, the system offers excellent flexibility; external devices -such as a push-button or a central timer – can be connected to an input to allow initiation of additional manual or automatic activations of the purging process.

## FEATURES AND BENEFITS

- A fully integrated and compact system, designed for larger pipe networks
- Designed for use in Honeywell Aspiration Smoke Detection (ASD) systems
- Patented design without air resistance (as defined by EN 54-20)
- 6 user selectable preventive or event-triggered purging programs
- Short or long purging cycle options
- Internal clock or external clock timer can be connected
- Several systems can be coupled in Master-Slave mode
- Manual control via external push-button
- Automatic initiation if a fault message is received from the ASD system (activating through FACP only)
- Easy commissioning without software tools
- Multi-colored LED indicates the system condition



# FAAST PURGING UNIT Technical Specification

PHYSICAL SPECIFICATION	
Height	68 mm
Width	204 mm
Depth	160 mm
Housing Cover Colour	Grey White, RAL 9002
Weight	3.2kg (approx.)
Patent Number	AT 514912

COMPRESSED AIR CONNECTION	
Max. Permissible Overpressure	0.7MPa (7.0bar)
Recommended Minimum	0.2MPa (2.0bar)
Flow Rate Solenoid Valve	0.2MPa: typ. 1,300 l/min
	0.4MPa: typ. 2,300 l/min
	0.6MPa: typ. 3,200 l/min
	0.7MPa: typ. 3,700 l/min


ENVIRONMENTAL SPECIFICATION	
<b>F-BO-AFE70-2</b>	
Operating Temperature	+5°C to +50°C
IP Rating	IP54
Relative Humidity	Max. 95% at 40°C
<b>F-BO-AFE70-3</b>	
Operating Temperature	-20°C to +40°C
IP Rating	IP54
Relative Humidity	Max. 95% at 40°C

ELECTRICAL SPECIFICATION	
Supply Voltage	21.6 – 30 VDC
Current Consumption @ 24v	8mA (normal condition)
	300mA (solenoid valve energised)

AIR DELIVERY PERFORMANCE	
F-BO-AFE70-2	(3500 lit/minute)
F-BO-AFE70-3	(5000 lit/minute)

ORDER CODES	
PRODUCT DESCRIPTION	ORDER CODE
Purging Unit / AFE70-2	F-BO-AFE70-2
Purging Unit / AFE70-3	F-BO-AFE70-3

## SYSTEM CONFIGURATION



**For more information**  
Contact your Business Manager

**Honeywell**  
140 Waterside Road  
Hamilton Industrial Park  
Leicester, LE5 1TN  
Tel: +44 (0) 203 409 1779

All technical data is correct at the time of publication and is subject to changes without notice. All trademarks acknowledged. Installation information: In order to ensure full functionality, refer to the installation instructions as supplied.

FAAST ASD PURGING UNIT | V.02 | 05/20  
© 2020 Honeywell International Inc.

**Honeywell**