

EshaFlex ProSafe Lightning Conductor Clips

Product Data Sheet



EshaFlex ProSafe

Lightning Conductor Clips

General Information

EshaFlex ProSafe Lightning Conductor Clips provide an easy to use, fast and simple, method to secure lightning conductor tape to EshaFlex roof systems. Manufactured from a high quality polymer that delivers excellent UV repellent properties that prevent the clips from fading and going brittle in the sun's rays. The clip is secured to the 100mm x 100mm membrane flange using a unique recessed rivet to eliminate damage to the EshaFlex Reinforced Bitumen Membrane (RBM) waterproofing membrane.

CODE	FLANGE DESCRIPTION	FLANGE SIZE (MM)	INSTALLATION METHOD	SUGGESTED FIXING CENTRES (MM)
LC-SBS-CHARCOAL	Felt - charcoal	100 x 100	Torch Applied	500
LC-SBS-GREEN	Felt - green	100 x 100	Torch Applied	500
LC-SBS-BRINDLE	Felt - brindle	100 x 100	Torch Applied	500

Supplied in a box containing 50 EshaFlex ProSafe Lightning Conductor Clips.

This information given in good faith and is based on the latest knowledge available to Radmat Building products Ltd. Whilst every effort has been made to ensure that the contents of the publication are current while going to press, customers are advised that products, techniques and codes of practice are under constant review and liable to change without notice.

For further information on Radmat products and services please call **01858 410372**, email techenquiries@radmat.com or visit our website www.radmat.com

JULY 22