



Specialists in Roofing
and Waterproofing

PermaQuik System Information

Radmat Electric Heating
Agitating Hot Air Melters



Radmat Electric Heating Agitating Hot Air Melters

Radmat Building Products own a fleet of Agitating Hot Air Melters that are available to hire on a weekly basis. All machines are serviced on return from hire and are maintained to the highest possible standards.

Hired machines should be returned with the drums emptied of any PermaQuik PQ6100 Hot Melt material, leaving molten material to set within the machine can damage the agitators and/or motors.

1.5 drum machines are available on a first come first serve basis.



Hot Rubber Melter	
Drive	Fully Electric
Chassis	Caster Mounted 2 x 200mm fixed, 2 x 200mm swivel/braked
Power	415 volt 3 phase - 32 amps (load 20kW)
Control Panel	Digital – Temperature Control
Burner	Electric heating element
Capacity	1.5 Drum
Main Frame	40 x 40 x 2mm RHS
Pan	5mm plate
End plates	Profiled 6mm
Outside case sheet	2mm
Outlet	Profiled
Forklift Locating Sleeves	Channel
Drive	415/30/3 phase motor – gearbox
Insulation	High temperature Rockwool dense slab
Stirrer Shaft	40mm BMS
Stirrer Shaft Bearings	40mm Pillar block
Lifting Eyebolts	M20 metric collared
D Shackles	3.25 ton green pin safety
Overall Length	2520 mm
Width	870 mm
Overall Height	1520 mm
Weight	687 kg



This information given in good faith and is based on the latest knowledge available to Radmat Building products Ltd. Whilst every effort has been made to ensure that the contents of the publication are current while going to press, customers are advised that products, techniques and codes of practice are under constant review and liable to change without notice.

For further information on Radmat products and services please call **01858 410372**, email techenquiries@radmat.com or visit our website www.radmat.com

JAN 24