

PRODUCT & COLOUR GUIDE







Now part of the Hempel Group, a world leading coatings supplier for the decorative, protective and marine markets, Crown Paints can trace its history over 200 years. It goes without saying that our highest priority still remains the production of high quality paints that meet our customers' needs.

Crown Trade is our premium quality professional paint brand.

Developed to give vibrant colour, excellent coverage and consistent quality, Crown Trade is widely specified in both domestic and commercial environments and used by contractors, decorators and builders. Crown Trade is backed by market leading advice and a service that is second to none.

Crown Trade offers a complete range of proven premium quality products, ideal for every decorating situation, from our Covermatt emulsion for use in new build environments to our market leading Timonox Flame Retardant Coatings range, which can slow down the spread of flames, protecting buildings and lives in the event of a fire.

Inside you'll find key reference information about the Crown Trade product range, grouped into seven clear sections: Primers & Preparation, Walls & Ceilings, Trim, Floor Coatings, Exterior Paints, Protective Coatings for Metal and Fire Retardant Coatings. We have also included information to help you with your project, such as guidance and tools to help you choose the right colour for your job.



ABOUT CROWN TRADE



THE RIGHT PAINT FOR YOUR JOB

CONTENTS

Choosing Colour with Crown Trade	04
Primers and Preparation	06
W Walls and Ceilings	12
*** Trim	18
Exterior Paints	26
Protective Coatings for Metal	28
Floor Coatings	31
Flame Retardant Coatings	32
Market Tecorator of the Year	38
Colour Influences	39
Tools & Services	40
W Our Brands	42
W General Information	44



Colour has a huge role to play in the built environment. As well as creating aesthetically pleasing spaces, colour can also be used to aid navigation, emphasize function, create a particular mood or ambience and to visually "correct" dimensions.

Give consideration to the following factors before choosing colour.

What is the room to be used for?

Colour can further promote the function of a space and elements of colour psychology can influence behaviour:

- · Blue is the colour thought to affect us most intellectually
- Red is dynamic and energising
- · Green is perceived as restful and calming
- · Yellow is optimistic and emotionally stimulating

There is also a strong relationship between colour and the perception of temperature. Colours such as reds, oranges and yellows are seen as being warm colours, increasing the perceived temperature of a space, whilst the opposite is true of greens and blue



Cool colours soothe the senses and calm down any potential areas of tension. These hues also aid concentration making them perfect for areas of work and study.



Warm colours can make a chilly room seem more comfortable and inviting. In a sociable environment, these colours will further help promote the room's function and help people to relax and unwind.

POWER OF COLOUR

What is the size of the space?

Colours can visually correct the dimensions of a space. Warm saturated colours can make walls appear closer whilst cold pale colours make them appear to recede.

What is the lighting like?

Understanding how light affects the colours we see and being aware of the location of a room and when it's most likely to be used will help make a more informed colour choice.

North facing rooms receive only skylight and reflected daylight which projects a cold grey colour cast onto all surfaces and colours. Use warm colours in the decor to compensate for the coolness of the light.

South facing rooms receive direct afternoon sunlight which will make yellows and reds look richer and more vibrant whilst blues and greens will look to have a yellow tint.





Grip Extreme Fast Drying Primer

Water-based

This product is a rapid drying, adhesion promoting primer that will lock in stains such as nicotine and tannins. It is ideal for use over difficult substrates including; glass, ceramic tiles, melamine, previously painted surfaces and chalky substrates, as well as most wood and non-ferrous metals.



- For interior and exterior use
- Fast drying recoatable in 1 hour
- Excellent adhesion
- Blocks stains




P.S.B Stain Block Primer

Water-based

A high performance primer for use on interior and exterior broadwall and trim areas. With excellent opacity and stain blocking properties it creates the ideal primer to cover and seal problem stains such as nicotine and smoke.



- For interior & exterior use
- · Locks stains into the paint film
- Excellent adhesion
- · Resists cracking and blistering
- Can be overcoated with water-based or solvent-based paint finishes



PRIMERS AND PREPARATION

Alkali Resisting Primer

Solvent-based

Ideal for priming, sealing and stabilising new, dry alkaline surfaces such as new lime plaster, cement and concrete. It can also be used to seal stains, stabilise powdery chalky surfaces and promote adhesion to glass, ceramics and some plastics.



- For interior and exterior use
- · Good adhesion & opacity
- · Resists alkaline attack
- Seals stains such as water and nicotine

APPLICATION	SPREADING RATE	
7	Up to 13m²/litre	
DRYING TIME		
Touch dry: 4-6hrs	Recoatable: 16hrs	
COLOUR RANGE		PACK SIZES
Off white		1L & 5L


Covermatt Drywall Primer

Water-based

Specially formulated for levelling out surface porosity on dry lined walls & ceilings. Provides the perfect base for first decoration products and Ideal for use under Crown Trade Covermatt Obliterating Emulsion.



- For interior use
- Reduces the appearance of roller striping in critical lighting
- Can also be a mist coat for new plaster where access to water is difficult





Fungicidal Solution

Water-based

A concentrated solution for the treatment of organic growth on interior and exterior unpainted and previously decorated surfaces.



- Approved under the control of pesticides regulations 1966
- Effectively kills algae and mould growth
- Registered with the HSE (HSE No. 10438)
- Easy to use

=40, 10 400	
APPLICATION	SPREADING RATE
T	Up to 30m²/litre
DRYING TIME	

24hrs (leave then rinse with clean water and allow to dry)

COLOUR RANGE	PACK SIZES
Clearonly	5L

Stabilising Solution

Solvent-based

Specially formulated stabilising primer for binding porous, loose and powdery surfaces prior to over painting.



- For interior and exterior use
- Apply one coat only
- Use on plaster, masonry and most exterior grade building boards
- Ideal for porous or chalking surfaces

APPLICATION	SPREADING RATE
7	Up to 6m²/litre
DRYING TIME	
Touch dry: 2hrs R	ecoatable: 16hrs
COLOUR RANGE	PACK SIZES
Clear and Off White	SI

PRIMERS AND PREPARATION

Acrylic Primer Undercoat

Water-based

An economical quick drying general purpose primer/undercoat, suitable for interior wood, hardboard and plaster. Not suitable for metal, plastic and loosely bound surfaces.



- · For interior use
- Quick drying
- Recoatable in 4 hours
- Good opacity and adhesion
- Economical for walls

APPLICATION	SPREADING RATE
Synthetic	Up to 16m²/litre
DRYING TIME	
Touch dry: 1hr R	ecoatable: 4hrs
COLOUR RANGE	PACK SIZES
White	1L, 2.5L & 5L

Red Oxide Primer

Solvent-based

An economical red oxide paint specially formulated for the protection of interior and exterior metalwork.



- For interior and exterior use
- Excellent obliteration
- Protects against corrosion
- A good holding primer prior to finishing

APPLICATION	SPREADING RATE
7	Up to 12m²/litre
DRYING TIME	
Touch dry: 4hrs	Recoatable: 16hrs
COLOUR RANGE	PACK SIZES
Dod	FI



Wood Primer

Solvent-based

A premium quality wood primer for use on softwood, plywood, chipboard and flakeboard.



- For interior and exterior use
- Seals the surface to provide excellent adhesion
- Excellent opacity
- Provides a sound foundation for painting

APPLICATION	SPREADING RATE
	Up to 10-12m²/litre
DRYING TIME	
Touch dry: 4-6hrs	Recoatable: 16hrs
COLOUR RANGE	PACK SIZES
White	1L, 2.5L & 5L

Aluminium Wood Primer

Solvent-based

Designed for interior and exterior priming of hardwoods, resinous softwoods and wood treated with wood preservative.



- For interior and exterior use
- Self-knotting
- Excellent adhesion
- Primes resinous wood
- Seals stains and tannins in the timber

	_
APPLICATION	SPREADING RATE
T	Up to 13m²/litre
DRYING TIME	
Touch dry: 2-4hrs	Recoatable: 16hrs
COLOUR RANGE	PACK SIZES
Grey	2.5L & 5L

PRIMERS AND PREPARATION

Universal Metal Primer

Solvent-based

A top quality metal primer for use on most ferrous and non-ferrous metals, alloys and suitably prepared galvanised steelwork.



- Suitable for interior and exterior use
- Excellent adhesion
- Rust inhibiting properties
- Reduces risk of corrosion

APPLICATION	SPREADING RATE
—	Up to 12m²/litre
DRYING TIME	
Touch dry: 2-3hrs	Recoatable: 6hrs
COLOUR RANGE	PACK SIZES
Grey	1L & 5L





Clean Extreme Stain Resistant Scrubbable Matt

Water-based

Clean Extreme Scrubbable Matt offers a finish that is 100% more stain resistant compared to conventional matt vinvl emulsion. It has superior cleaning capabilities which do not compromise the integrity or finished appearance of the paint film.



- 100% more stain resistant
- New and aged stains can be easily cleaned away
- · Extreme durability in high traffic areas
- 10,000 scrubs durability
- ISO 11998 class 1 scrub rating





SPREADING RATE







Touch dry: 1-2hrs

Recoatable: 4hrs

COLOUR RANGE

PACK SIZES

See Crown Trade Colour Collection Fan

2.5, 5L & 10L

Clean Extreme Stain Resistant Acrylic Eggshell

Water-based

Clean Extreme Acrylic Eggshell offers a finish that is 100% more stain resistant compared to conventional matt vinyl emulsion. It has superior cleaning capabilities which do not compromise the integrity or finished appearance of the paint film.



- 100% more stain resistant
- Extreme durability in high traffic areas
- · Subtle mid sheen finish
 - ISO 11998 class 1 scrub rating

APPLICATION

SPREADING RATE

51







Up to 14m²/litre

DRYING TIME

Touch dry: 1-2hrs

Recoatable: 4hrs

COLOUR RANGE

PACK SIZES

See Crown Trade Colour Collection Fan

WALLS AND CEILINGS

Clean Extreme Mould Inhibiting Scrubbable Matt

Water-based

Clean Extreme Mould Inhibiting Scrubbable Matt offers a dual purpose solution that is stain resistant and defends against mould growth. Formulated using advanced slow release technology, suitable for interior walls and ceilings.

APPLICATION



• Ideal for Kitchens, Bathrooms and void premises

SPREADING RATE

SPREADING RATE

- Extreme fungicidal barrier defence
- Superior Stain Resistance
- New and aged stains can be easily cleaned away
- ISO 11998 class 1 scrub rating



Clean Extreme Mould Inhibiting Acrylic Eggshell

Water-based

Clean Extreme Mould Inhibiting Acrylic Eggshell offers a dual purpose solution that is stain resistant and defends against mould growth. Formulated using advanced slow release technology, suitable for interior walls and ceilings.



- Ideal for Kitchens, Bathrooms and void premises
- Extreme fungicidal barrier defence
- Superior Stain Resistance
- New and aged stains can be easily cleaned away
- ISO 11998 class 1 scrub rating



APPLICATION



Clean Extreme Anti-Bacterial Scrubbable Matt

Water-based

Clean Extreme Anti Bacterial Scrubbable Matt offers a dual purpose solution that is stain resistance and defends against bacteria such as MRSA and Ecoli, using independently tested SteriTouch® silver ion technology, suitable for interior walls and ceilings.



- SteriTouch® silver ion technology
- MRSA & Ecoli defence coating
- Superior Stain Resistance
- New and aged stains can be easily cleaned away
- Independently tested to ISO 11998 class 1 scrub rating



APPLICATION SPREADING RATE Up to 14m²/litre





DRYING TIME

Touch dry: 2hrs

Recoatable: 4hrs

COLOUR RANGE

PACK SIZES

51

See Crown Trade Colour Collection Fan

Clean Extreme Anti-Bacterial Acrylic Eggshell

Water-based

Clean Extreme Anti Bacterial Acrylic Eggshell offers a dual purpose solution that is stain resistant and defends against bacteria such as MRSA and Ecoli, using independently tested SteriTouch® Silver Ion Technology, suitable for interior walls and woodwork.



- SteriTouch® silver ion technology
- MRSA & Ecoli defence coating
- Superior Stain Resistance
- · New and aged stains can be easily cleaned away
- ISO 11998 class 1 scrub rating





SPREADING RATE







DRYING TIME

Touch dry: 1-2hrs

Recoatable: 4hrs

COLOUR RANGE

PACK SIZES

See Crown Trade Colour Collection Fan

51

WALLS AND CEILINGS

Matt Vinyl

Water-based

A premium quality flat matt emulsion for interior use on wall and ceiling surfaces, where a flat non-reflective finish is required.



- Excellent opacity
- Quick drying

APPLICATION

- Good colour retention
- Easy application
- True flat matt finish
- Available in handy 250ml tester pots

Up to 17m²/litre **DRYING TIME** Touch dry: 1-2hrs Recoatable: 4hrs **COLOUR RANGE**

PACK SIZES

SPREADING RATE

See Crown Trade Colour Collection Fan

250ml, 1L 2.5L, 5L & 101

Silk Vinyl

Water-based

A premium quality silk emulsion for interior use on wall and ceiling surfaces, where a washable high sheen finish is required.



- · Washable finish
- Quick drying





Mid Sheen Vinyl

Water-based

A mid-sheen emulsion for use on interior walls and ceilings.



- · Wipeable finish
- Quick drying
- · Good opacity and colour retention



Acrylic Eggshell

Water-based

A premium quality fast drying, virtually odour free paint. A highly durable eggshell finish for use on interior broadwall areas and ioinerv.



Virtually solvent free



WALLS AND CEILINGS

Covermatt Emulsion

Water-based

An emulsion specially formulated for the first time decoration of new build interiors, allowing them to dry out without compromising the paint surface. Ideal for new plaster.



- · Exceptionally high opacity
- Quick drying
- · Easy to apply
- Low spatter

APPLICATION

SPREADING RATE

7

11-16m²/litre dependent on surface porosity

DRYING TIME

Touch dry: 1-2hrs

Recoatable: 4hrs

COLOUR RANGE

See Crown Trade Colour Collection Fan

PACK SIZES
500ml*, 5L & 10L

*500ml available in white & magnolia only





Fastflow Quick Dry Gloss

Water-based

A water-based, durable gloss finish for use on suitably prepared interior and exterior joinery and metalwork. Fastflow Quick Dry Gloss has excellent opacity, and has all the benefits of a water-based formulation including quick drying and low odour with a traditional finish.



- Interior and exterior use
- Feels like a traditional gloss
- Quick drying
- Excellent flow

COLOUR RANGE

See Crown Trade Colour Collection Fan

· High sheen





Fastflow Quick Dry Satin

Water-based

Awater-based, contemporary satinfinish for use on suitably prepared interior and exterior joinery metalwork. A contemporary finish which is quick drying, low odour, excellent opacity, and provides all the benefits of a water based formulation.



- Interior and exterior use
- Breatheasy formulation
- Advanced waterbased technology
- Contemporary satin finish



APPLICATION	SPREADING RATE
Medium Pile synthetic	Up to 15m²/litre
DRYING TIME	
Touch dry: 1-2hrs Re	ecoatable: 4-6hrs



COLOUR RANGE

PACK SIZES 1L, 2.5, & 5L

PACK SIZES

1L, 2.5, & 5L

See Crown Trade Colour Collection Fan

Fastflow Quick Dry Primer Undercoat

Water-based

A water-based primer undercoat with excellent coverage and quick drying properties, specially formulated for use with Crown Trade Fastflow Quick Dry Gloss and Satin. Suitable for interior and exterior joinery and correctly prepared metalwork.



- Interior and exterior use
- Feels like a traditional undercoat
- Quick drying

APPLICATION

 Ideal basecoat for Crown Trade Fastflow Quick Dry Gloss and Satin

SPREADING RATE







Full Gloss

Solvent-based

A premium quality decorative finish for use over correctly prepared joinery and metal. Providing a beautiful high gloss finish.



- For interior and exterior use
- Exceptionally hard wearing
- Excellent opacity and film build
- High gloss and colour retention
- Good flow properties

APPLICATION	SPREADING RATE
7	Up to 12-15m²/litre. Do not over apply
DRYING TIME	
Touch dry: 6hrs	Recoatable: 16 -24hrs* *Ensure previous coat is fully dry before appliction
COLOUR RANGE	
See Crown Trade Colour Col	llection Fan 1L, 2.5, & 5L

Full Undercoat

Solvent-based

A premium quality undercoat for use over correctly prepared and primed joinery and metal.



- For interior and exterior use
- Excellent obliteration
- Good wet edge retention
- Excellent adhesion and opacity

APPLICATION	SPREADING RATE	
7	Up to 18m²/litre	
DRYING TIME		
Touch dry: 4-6hrs R	Recoatable: 16hrs	
COLOUR RANGE	PACK SIZES	

See Crown Trade Colour Collection Fan

New Build Acrylic Gloss

Water-based

Specially formulated to combat the accelerated yellowing sometimes associated with new build environments, when applied over Crown Trade New Build Acrylic Primer Undercoat. The system is guaranteed to show no visible yellowing.



- For interior and exterior use
- Non-yellowing
- Quick-drying
- · Durable, flexible finish
- Can be applied in temperatures down to 8°C



Use with New Build Acrylic Primer Undercoat

Next Generation Plus System

Solvent-based

Part of a premium gloss system, which offers excellent application and flow properties, along with a beautiful high gloss finish. For the perfect finish use with Next Generation Plus Undercoat.



- For interior and exterior use
- Excellent application and flow
- Easy to apply
- Excellent gloss retention





Acrylic Satin Finish

Water-based

Crown Trade Acrylic Satin Finish is a virtually solvent free alternative to traditional solvent-based satin finish, offering a smooth elegant finish for interior and exterior wood and correctly primed metalwork.



- For interior and exterior use
- Non yellowing
- Quick drying
- Virtually solvent free

 Excellent flow 	
APPLICATION	SPREADING RATE
Medium Pile synthetic	Up to 14m²/litre.
DRYING TIME	
Touch dry: 1-2hrs R	ecoatable: 4-6hrs
COLOUR RANGE	PACK SIZES
White	1L & 5L

Satin Finish

Solvent-based

A tough, durable formulation, offering a washable satin finish for interior woodwork and metal.



- For interior use
- Excellent durability
- · Elegant satin finish
- Does not always require an undercoat
 self undercoating
- Good flow

APPLICATION	SPREADING RATE
Up to 16m²/litre	
DRYING TIME	
Touch dry: 6hrs Recoatable: 16hrs	
COLOUR RANGE	PACK SIZES
See Crown Trade Colour Colle	ction Fan 1L, 2,5L, & 5L

Eggshell

Solvent-based

A premium quality, highly durable, washable eggshell finish for interior use. It offers outstanding resistance to steam and condensation and is suitable for areas such as kitchens and bathrooms and high traffic areas. For large areas we recommend the use of Acrylic Eggshell.



- For interior use
- · Excellent durability and opacity
- Good flow and adhesion
- · Long lasting washable finish
- Smooth sheen finish

• SITIOOUT SHEET HITISH		
APPLICATION SPREADING RATE		
	Up to 16m²/litre	
DRYING TIME		
Touch dry: 6hrs Recoatable: 16hrs		
COLOUR RANGE	PACK SIZES	
See Crown Trade Colour Collec	ction Fan 1L, 2.5L, & 5L	

Aluminium Paint

Solvent-based

A high quality aluminium paint for use where a durable and metallic effect finish is required. Also suitable for heated pipework.



- For interior and exterior use
- Exceptional opacity
- Durable metallic effect finish
- Suitable for temperatures up to 250°C

APPLICATION	SPREADING RATE	
	Up to 15m²/litre	
DRYING TIME		
Touch dry: 4-6hrs	Recoatable: 16hrs	
COLOUR RANGE	PACK SIZES	
Aluminium	1L & 5L	



YOUR PERFECT COLOUR? MATCH IT WITH CROWN TRADE

We all have a favourite colour. If you can't find your perfect colour we can simply create it for you. Our colour mixing system means **we can match virtually any colour** you wish for, so you get a truly personal service.

It's not just paint.

It's personal.





MyRoomPainter **App**

An exciting way to help plan your painting project.







Download it **NOW**





It's not just paint.

It's personal



Stronghold Textured Masonry Paint

Water-based

A high quality and finely textured protective and decorative finish. For use on most exterior masonry surfaces and exterior grade building boards.



- Helps bridge fine hairline cracks
- 15 years proven durability
- Contains rock aggregate to ensure maximum weather protection

APPLICATION	SPREADING RATE		
7	Up to 6-8m2/litre on smooth surfaces, 3-4m2/litre on textured surfaces		
DRYING TIME			
Touch dry: 1-2hrs	Recoatable: 6hrs		
COLOUR RANGE		PACK SIZES	
See Crown Trade Pro	ofesional	5L	

Stronghold Smooth Masonry Paint

Water-based

A smooth, protective and decorative finish, for use on most exterior masonry surfaces and exterior grade building boards.

Painters Colour Guide



- Resists dirt retention
- 10 years proven durability
- Anti-carbonation certified
- Excellent weather resistance

Excellent weather resistance			
APPLIC	CATION		SPREADING RATE
	—	F	Up to 16m2/litre on smooth surfaces, 6m2/litre on textured surfaces
DRYING TIME			
Touch d	ry: 1-2hrs	1-2hrs Recoatable: 4-6hrs	

COLOUR RANGE PACK SIZES

See Crown Trade Profesional Painters Colour Guide 5L & 10L

EXTERIOR PAINTS

Stronghold Exterior Primer Undercoat

Solvent-based

Specially formulated for use with Stronghold Exterior Gloss. Formulated for the long-term protection of exterior timber.



- Provides a flexible base
- · Seals the wood
- Can be used as an undercoat on primed or unprimed wood and correctly prepared metal

APPLICATION	SPREADING RATE		
7	Up to 15m ² /litre		
DRYING TIME			
Touch dry: 4-6hrs	Recoatable: 16-24hrs		
COLOUR RANGE		PACK SIZES	
White & Dark Grey		2.5L	

Stronghold Exterior Gloss

Solvent-based

A high performance flexible gloss system incorporating a premium quality combined primer / undercoat and durable high gloss top coat. Formulated for the long-term protection of exterior timber.



- 6 years proven durability
- Can be used on suitably primed and undercoated metal
- Flexible finish for exterior wood

A DDI ICATION	CDDEADING DA	TE
APPLICATION	SPREADING RA	NIE.
	Up to 12-15m²/litre	
DRYING TIME		
Touch dry: 6hrs	r: 6hrs Recoatable: 16-24hrs	
COLOUR RANGE		PACK SIZES
See Crown Trade Pro		1L, 2.5L & 5L



Protective Coatings T-Wash

Water-based

Crown Trade Protective Coatings T-Wash is an etching wash for new bright unweathered, untreated galvanised surfaces. It creates a chemical reaction and causes the surface to turn black, which confirms that the surface has been degreased and etched. Treated surfaces are then ready for priming.



- Etching wash
- Reaction causes surface to blacken
- Confirms surface has been degreased and etched

APPLICATION	SPREADING RATE		
T	Up to 15-20m²/litre		
DRYING TIME			
Touch dry: 2hrs Surfaces must be primed within 48 hours			
COLOUR RANGE PACK SIZES			
Clear	5L		

High Build Micaceous Iron Oxide

Solvent-based

Crown Trade Protective Coatings High Build Micaceous Iron Oxide acts primarily as an intermediate coat on ferrous metals such as structural steelwork, fire escapes, railings and gates, providing a barrier against corrosion. It can also be used as a finish in its own right where a protective coating is required, but aesthetics are not important.



- Protects against corrosion
- Excellent intermediate coat.
- Use as a top coat where a decorative finish is not important
- Full system can protect up to 15 years

APPLICATION	SPREADING RATE	
	Up to 8m²/litre on smooth surfaces.	
DRYING TIME		
Touch dry: 4hrs	Recoatable: 16hrs	
COLOUR RANGE	PACK SIZES	
Grey	2.5L	

PROTECTIVE COATINGS FOR METAL

High Build Rust Inhibiting Metal Primer/Undercoat

Solvent-based

Crown Trade Protective Coatings High Build Rust Inhibiting Metal Primer/Undercoat has been developed for use as a spot primer to prepare failed, weathered cladding prior to painting with Fast Drying Cladding Finish. It is also recommended for use on ferrous and nonferrous metals, providing an excellent foundation for the protection of interior and exterior metalwork, particularly structural steelwork.



- Spot primer for Crown Trade Fast Drying Cladding Paint
- Excellent adhesion
- · Reduced risk of corrosion

• Full system can protect up to 15 years			
APPLICATION	SPREA	DING RATE	
Up to 7m²/litre			
DRYING TIME			
Touch dry: 3hrs Recoatable: 6hrs			
COLOUR RANGE		PACK SIZES	
Grey		2.5L	

High Performance Gloss for Metal

Solvent-based

Crown Trade Protective Coatings High Performance Gloss for Metal provides a durable and long lasting finish for all exterior metalwork, particularly structural steelwork, walkways, railings, gates and shutters. It has excellent adhesion and gloss retention and acts as a sound topcoat for the Crown Trade High Performance paint system for metalwork.



- Systems for up to 10 and up to 15 years protection available
- Excellent UV resistance
- · High gloss finish
- No sag formulation

APPLICATION SPREADING RATE Up to 12-15m2/litre on smooth surfaces. Do not over apply.

DRYING TIME

Touch dry: 4-6hrs

Recoatable: 16-24hrs. (ensure previous coat is fully dry before application)

COLOUR RANGE

PACK SIZES

See Crown Trade Professional Painters Guide

251





Fast Drying Cladding Finish

Water-based

Crown Trade Protective Coatings Fast Drying Cladding Finish is a high performance coatings system, specially developed for the refurbishment of pre-coated, weathered metal cladding, enabling it to be restored to a pristine condition. It is pleasant to use and fast drying, enabling a quick and easy transformation of tired cladding.



- Single pack
- Provides up to 8 years protection
- Fungal resistant properties
- Satin finish
- · No special application tools required

APPLICATION





SPREADING RATE

Up to 15m2/litre on smooth surfaces

DRYING TIME

Touch dry: 1-2hrs

Recoatable: 4-6hrs.

COLOUR RANGE

PACK SIZES

See Crown Trade Professional Painters Guide

5L

Epimac Floor Coating

Solvent-based

An easy to use, single pack epoxy esterbased floor coating with outstanding adhesion for use on interior floors.









- Durable finish
- · Low glare satin finish
- · Resistant to abrasion and scuffing
- · Resistant to spillages of oil, petrol and detergent

A	P	P	LI	C	A'	TI	0	N	

SPREADING RATE

Up to 15m2/litre

DRYING TIME

Touch dry: 4-6hrs

Recoatable: 16hrs

COLOUR RANGE

PACK SIZES

Mid Grey*, Tile Red*, Green, Dark Grey, Clear

* Also available in Anti Slip

Fast Drying Concrete Floor Paint

Solvent-based

A decorative floor paint for interior concrete floors in warehouses, shops and showrooms.



- For interior use
- · Hard-wearing finish
- Recoatable after 6 hours
- · Allows you to complete a project in one day

APPLICATION

SPREADING RATE



Up to 12 - 15m²/litre

DRYING TIME

Touch dry: 3hrs

Recoatable: 6hrs (with good airflow and warm conditions)

COLOUR RANGE

PACK SIZES

See Crown Trade Colour Collection Fan

51





ABOUT TIMONOX FLAME RETARDANT COATINGS

Crown Trade Timonox has a long, well established history of providing a first line defence against the spread of flame, and so offers a comprehensive solution to the perceived 'Duty of Care' for building owners, facility managers or employers to protect the occupants of their properties.



FLAME RETARDANT COATINGS



WHY USE TIMONOX

- · No special application techniques required
- Buys precious time for evacuation in the event of fire
- Offers a range of decorative paint finishes
- Has an extensive colour offering
- Offers anti-graffiti options
- Products are water-based or solvent free for ease of use
- Products have excellent coverage
- · Comprehensive technical and sales support available

Timonox products should only be used as part of fire tested systems. For more information please contact the Specification Services Team:

Tel: 0330 0240310

Email: info@crownpaintspec.co.uk

Or visit our website: www.crownpaintspec.co.uk



Timonox Vinyl Matt

Water-based

A decorative flame retardant coating for walls and ceilings, specially formulated for use on new non-combustible surfaces and previously painted non-combustible surfaces.



- · Inhibits the spread of flames in a fire
- · Ideal for use in communal areas
- Can be used as part of a system to upgrade existing coatings to class 0



Timonox Vinyl Silk

Water-based

A decorative, high sheen, flame retardant coating for walls and ceilings, specially formulated for use on new non-combustible surfaces and previously painted non-combustible surfaces.



- Inhibits the spread of flames in a fire
- · Ideal for use in communal areas
- Washable finish



5L

See Crown Trade Colour Collection Fan

FLAME RETARDANT COATINGS

Timonox Clear Top Coat

Water-based

A water-based, sacrificial glaze, providing additional protection and durability. For use over Timonox Acrylic Eggshell only.



- Inhibits the spread of flames in a fire when used over Timonox Acrylic Eggshell
- Ideal for use in communal areas where extra durability is required

APPLICATION	SPREADING RATE					
	Up to 10m²/litre (must not be exceeded)					
DRYING TIME						
Touch dry: 2hrs	ecoatable: 4-6hrs					
COLOUR RANGE	PACK SIZES					
Clear	5L					

Timonox Anti-Graffiti Flame Retardant Glaze

Solvent-based

A 100% solids, solvent-free, 2 pack non-sacrifical, high eggshell, flame retardant glaze for use over Crown Trade Timonox Vinyl Matt only. Provides a flame retardant surface from which graffiti and other soiling can be more easily removed.



- Provides flame retardant anti-graffiti top coat for use over Timonox Vinyl Matt to upgrade existing coatings to class 0
- One coat application





Timonox Bonding Primer

Water-based

Provides the ideal foundation for Timonox coating systems. This water-based adhesion promoting primer prepares both new and old surfaces such as plaster, cement, concrete and old paintwork, providing good obliteration and permanently blocking residual stains.



- Excellent adhesion properties
- Superior stain blocking
- Provides an ideal foundation for Timonox coating systems

APPLICATION	SPREADING RATE					
7 -	Up to 12m²/litre on smooth surfaces. (must not be exceeded)					
DRYING TIME						
Touch dry: 2hrs	ecoatable: 15hrs					
COLOUR RANGE	PACK SIZES					
White	5L					

Timonox Upgrade Basecoat

Solvent-free

Timonox Upgrade Basecoat upgrades class 4 surfaces to class 0 in an easy to use system. Formulated to produce a thick insulating char layer in the event of a fire and therefore protecting the underlying combustible substrate.



- Forms part of a system to upgrade existing coatings to class 0
- Must be overcoated, does not provide a durable decorative finish



FLAME RETARDANT COATINGS

Timonox Scrubbable Matt

Water-based

Timonox Scrubbable Matt is a premium product suitable for interior wall and ceiling surfaces where a durable, scrub resistant, waterbased and flame retardant matt finish is required.



- Scrub resistant (rating class 1 to ISO11998)
- Durable aesthetic finish
- Can be used as part of a system to upgrade existing coatings to class 0

. 1. 0					
APPLICATION	SPREADING RATE				
Airless	Max 14m²/litre on smooth surfaces. (must not be exceeded spray				
DRYING TIME					
Touch dry: 1hr Re	coatable: 4hrs				
COLOUR RANGE	PACK SIZES				
Colours only - see Crown Trade	Colour 5L				

Timonox Acrylic Eggshell

Water-based

A decorative flame retardant coating for walls and ceilings, specially formulated for use on new non-combustible surfaces and previously painted non-combustible surfaces.



- Inhibits the spread of flames in a fire
- Ideal for use in communal areas
- · Washable finish
- Can be used as part of a system to upgrade existing coatings to class 0

APPLICATION	SPREADING RATE			
(Airle	Up to 14m²/litre on smooth surfaces. (must not be exceeded)			
DRYING TIME				
Touch dry: 1hr	Recoatable: 4hrs			
COLOUR RANGE	PACK SIZES			
See Crown Trade Colour Colle	ection Fan 5L			



EARN

HAVE YOU GOT WHAT IT TAKES TO **BECOME THE NEXT CROWN PAINTS** APPRENTICE DECORATOR OF THE YEAR?

For more information visit:

WWW.CROWNTRADE.CO.UK

or call 0330 024 0297

In association with







It's not just paint. It's personal

COLOUR COLLECTION & TRENDS


We believe paint is not just about decoration, it's about using colour to turn an ordinary space into something personal.

Our expert panel, made up of consultants, specialists and designers have colour at the heart of everything they do.

For more information on Crown Paints Colour Influences or to request a brochure, please contact **0330 024 0297** or email **info@crowntrade.co.uk**









SPECIFICATION SERVICE SOLUTIONS FOR YOUR PROJECT

We want our customers to be totally happy with our products and services, and go the extra mile to ensure that your decorative and protective needs are satisfied.

WE OFFER AS STANDARD...

- Dedicated specification support
- Site visits including conditions surveys and flake analysis
- Full technical specifications and asset management programmes
- Training specifying clients and painting contractors
- Assessing climatic, atmospheric and environmental conditions to ensure correct specification
- On-going site support and setting key performance indicators



TOOLS AND SERVICES







CROWN TRADE WEBSITE...

Visit **www.crowntrade.co.uk** for information on all of our products with tools such as an easy to follow product filter and a convenient pick list, to help you to find the perfect solution for your project. You can also find out about the latest colour trends, to ensure that you and your customers are making the correct

colour choices, by using our Inspirational area of the site.

Visit **www.crowntrade.co.uk** now to find the right paint for your job!



sandtex trade

Sandtex

For exterior masonry, wood & metal

When your work takes you out of doors there's only one name you need to remember – Sandtex Trade.

This superior range of paints, protective coatings, preparatory and repair materials has everything you need for all your exterior decorating and maintenance projects and has been protecting buildings for over 50 years.

www.sandtextrade.co.uk





sadolin



Superior wood protection

Renowned throughout the professional and DIY markets for offering the very highest possible standard of wood protection, products bearing the Sadolin name benefit from the most recent advances in coatings technology ... yet at the same time boast a rich history and heritage stretching back over 200 years.

www.sadolin.co.uk







Environmental Product Declarations (EPDs)...

6 of our products hold verified EPD certificates complying with the European Standard EN 15804:



The EPDs are aligned with the environmental requirements of BREEAM and LEED and also meet the requirements of the SKA rating scheme, meaning these products can be confidently specified in projects where environmental considerations are key. The Crown Paints EPD certificates can be found online at Green BookLive, a unique listing of environmental products and services.

Ska Rating... Partie are included in the Materials issue of the Ska Rating (M14). There are three criter at to choose from in order to be compliant with the scheme, one of which is that the paint should carry an environmental product declaration (EPD) written in accordance with ISO 14025. Our six products that hold EPDs, as mentioned above, comply with this criteria.

environment through the specification and installation of internal finishes that meet the specified criteria for emissions of volatile organic compounds (VOCs). We are happy to say that all of Crown Paints' products comply with the relevant requirements.


BES 6001 Responsible Sourcing... We are pleased to announce that we hold BES 6001 Responsible Sourcing certification for our water-based products manufactured at Hull. This certification compliments our ISO 9001 and ISO 14001 Quality and Environmental management systems in demonstrating that we are a responsible business, raising our profile in terms of our sustainability and environmental credentials for tenders and specification, particularly for projects where sustainable issues are a key feature, such as those looking to gain green building scheme accreditations.

GENERAL INFORMATION

We care about our environment and community

- Sustainability
- · Charity & Community
- · Education, Skills & Apprenticeships
- · The Hempel Foundation

For more information please visit the **Corporate** section of **crownpaint.co.uk**





NOTES		
-		

NOTES

NOTES		



Crown Trade Customer Relations Team Telephone: 0330 0240297; Fax: 0330 0240278; info@crowntrade.co.uk; www.crowntrade.co.uk



Use the Crown Paints PaintSpec Finder® at www.crownpaintspec.co.uk



By Appointment to Her Majesty The Queen Manufacturers of Paints Crown Paints Limited Darwen, Lancashire



FM 543424 ISO 9001





CrownTradePaint



CrownTradePaint

Find us on:







Crown Paints Ltd, PO Box 37, Hollins Road, Darwen, Lancashire, BB3 OBG. Telephone: 01254 704951 Fax: 01254 774414

Crown Paints Ireland Ltd, Malahide Road, Coolock, Dublin 17 Telephone: 01 8164400 Fax: 011 8478831



All trademarks and logos featured in this publication are the property of, or licensed to Crown Paints Limited.

©Copyright 2018 Crown Paints Ltd. Material Code 6054525

