
Invicta Technical Data Guide

brettlandscaping.co.uk






built on relationships



Colours



Citrine














*Light traffic suitable for Invicta TRIO 60mm and 600x200x80mm **80mm up to and including 300x200 can be used in a flexible heavy duty application.

Pearl



Standards and Performance

Product Type	Precast Concrete Paving Blocks/Flags	e
Manufacturing Standard	BS EN 1338 : 2003 / BS EN 1339 : 2003	
Design Standards	BS 7533-101:2021 ; BS 7533-13:2009	TRA
Installation Standards	BS 7533-3:2005 +A1:2009 ; BS 7533-4:2006	
Application	Domestic and Commercial use; hardstanding for vehicular & pedestrian pavements including footpaths, cycle tracks, driveways, adoptable highways, commercial pavements, roof top and balcony applications etc. (Please see www.brettlandscaping.co.uk for further guidance on applications suitable for paving plan sizes.)	HE/ TR/
Strength	Characteristic tensile splitting strength \geq 3.6 Mpa; Failing load \geq 250 N/mm	PEDE L
Strength 600x200x80mm	Characteristic bending strength \ge 5.0 Mpa / Characteristic breaking load > 4.5 KN	
Abrasion Resistance	\leq 23mm - Determined by Wide Wheel Abrasion Test	н
Durability	Class $3 \le 1.0$ kg/m ² with no individual result ≤ 1.5 kg/m ²	SLIF RESIS
Slip/Skid Resistance	Unpolished Slip Resistance Value \geq 55 - Potential for slip - Low	
Slip/Skid Resistance 600x200x80	≥ 55 - Potential for slip - Low	Agg
Reaction to Fire	Class A1 when used for internal flooring	LA
External Reaction to Fire	Deemed to satisfy	_
Emission of asbestos	No content	
Thermal Conductivity	1.2 W/(mK)	

Sustainability

BES 6001	Responsible Sourcing of Concrete Products (Rating: Excellent)
Energy Use	100% renewable electricity
Recyclable	100% of this product can be recycled
Manufacturing	Produced in the UK using responsibly sourced materials
Waste Wood + Plastic	100% recyclable
Carbon Footprint	Brett Landscaping and Building Products have contributed to the members' of Interpave, a product group of British Precast, Environmental Product Declaration for Paving Products (Blocks, Slabs, Channels and Kerbs), in accordance to BS EN 15804:2012-4+A1 2013, independently verified according to ISO 14025:2011-10. To download the Environmental Product Declaration visit www.brettlandscaping.co.uk/download
BREEAM	Concrete Block Paving 60mm: A rating, as per the BRE Green Guide, 4th Edition 2009, A+ rating can be achieved when used in conjunction with a prepared recycled sub-base. Concrete Block Paving 80mm: B rating, as per the BRE Green Guide, 4th Edition 2009, A rating can be achieved when used in conjunction with a prepared recycled sub-base.

*Light traffic suitable for Invicta TRIO 60mm and 600x200x80mm **80mm up to and including 300x200 can be used in a flexible heavy duty application.
















Finishes

Beautifully Engineered, the Brett Invicta range uses a specially formulated surface layer, AggTech, which has been developed to deliver high performance with a stunning, individual aesthetic. Invicta has been developed to perform, using only the highest-quality materials. You'll appreciate its distinctive sparkle, and the colours in its range have been specifically developed to complement each other, enabling a flexibility of design like nothing else.

Certification

BES 6001	Responsible Sourcing of Concrete Products
ISO 9001	Quality Management.
ISO 14001	Environmental Management.
ISO 45001	Occupational Health and Safety Management.
CE Marking UKCA Marking	Contact us for Declaration of Performance (DOP) data. Contact us for Declaration of Performance (DOP) data.









To ensure its long-life structural performance, Invicta's AggTech surface layer includes more cement, a higher concentration of pigment for richer, more defined tones, and a finer cut of premium, globally sourced, specialist aggregates. Formed in unison to the coarse, robust sub-layer, results in an extremely strong and secure bond for the life of the paving.

Its surface layer is extremely hardwearing enabling it to shrug-off extreme weather and retain its vivid, brighter colours.


Tough and beautiful for longer

wants Bro are , i i of Finer Aggregates BARRISS SAME - LEASE LAND PARTY High Pigment Content More Cement

*Light traffic suitable for Invicta TRIO 60mm and 600x200x80mm

**80mm up to and including 300x200 can be used in a flexible heavy duty application.





Stock Information

Invicta Block Paving									
Depth (mm)	Size (mm)	Colours	No. Per Pack	No. Per m ²	m ² Per Pack	Pack Weight (kg)	Pack Type		
80	200 x 100	Pearl Moonstone Onyx Citrine	336	50	6.72	1327	Pallet		
	200 x 200		168	25					
	300 x 100		224	33.33					
	300 x 200		112	16.67					

Invicta Flag Paving									
Depth (mm)	Size (mm)	Colours	No. Per Pack	No. Per m ²	m ² Per Pack	Pack Weight (kg)	Pack Type		
80	600 x 200	Pearl Moonstone Onyx Citrine	56	8.33	6.72	1328	Pallet		

Invicta Flow Block Paving									
Depth (mm)	Size (mm)	Colours	No. Per Pack	No. Per m ²	m ² Per Pack	Pack Weight (kg)	Pack Type		
80	215 x 115	Pearl Moonstone Onyx Citrine	336	50	6.72	1266	Pallet		

Invicta TRIO Block Paving

Depth (mm)	Size (mm)	Colours	No. Per Pack	No. Per m ²	m ² Per Pack	Pack Weight (kg)	Pack Type
60	105x140	Pearl Moonstone Onyx Citrine	108	68	9.53	1410	Pallet
	140x140		162	51			
	210x140		162	34			

CPC ? CPC ?

*Light traffic suitable for Invicta TRIO 60mm and 600x200x80mm **80mm up to and including 300x200 can be used in a flexible heavy duty application.









Possibilities, simply inspired.

AN VIZ

All Brett Landscaping products, along with products from across the Brett Group, have been extensively tested and proven to conform to the relevant UK Standard(s). This is our customers' assurance that they are safe to use and fit for purpose.

Continue to be inspired. Get social and experience the possibilities of Brett products.





10/2021

brettlandscaping.co