

Technical Data – Release Agent

PRODUCT DESCRIPTION

PICSPAVE Release Agent (RA) is a pre-mixed, coloured blend of sub-micronic powders.

PURPOSE

To allow easy and free release of **PICSPAVE** Textured Imprinting Mats from the wet surface of concrete after application and finishing of **PICSPAVE CSH** and to create secondary pigmentation of the low points of the textured surface by imparting a contrasting colour.

SPECIAL PROPERTIES

- Allows deep and complex imprints and easy imprinting mat removal without surface tearing
- Will not cake or become brittle on wet surfaces
- Excellent surface adhesion – not removed by wind once applied
- 100% Hydrophobic to create a total moisture barrier
- Available in 12 standard colours that are inter-compatible and can be blended with confidence to create special colours
- Free flowing yet cohesive – does not segregate upon application
- Ultra Violet (UVA) stable pigments conform to BS1014 guarantee colours will not fade as a result of direct sunshine

APPLICATION INSTRUCTIONS

After the CSH has been applied to the concrete, floated, trowelled and tested for firmness, **RA** should be applied after being thoroughly hand mixed in its container. **RA** should be gently cast onto the concrete surface, do not cast over long distances as it will become airborne. Do not over apply – only a very thin layer is needed, enough has been applied when the **CSH** colour is masked by the colour of the **RA**. When the area to be printed has been covered with **RA**, the first imprinting mat can be placed.

APPROXIMATE COVERAGE

6m² to 7m² per kg.

STORAGE

Store in a cool, dry area and avoid exposure to heat or flame.

PACKAGING

10kg Snap Lock Plastic Pail.

SPECIFICATION CLAUSE

*"Immediately prior to imprinting, the concrete shall be dusted with **PICSPAVE RA** which shall combine imprinting mat release without surface tearing, anti-caking and surface adhesion capabilities and impart a secondary colour in the low points of the textured surface.*

All the work shall be carried out in accordance with the manufacturers current technical data sheet, specification and instructions for use by trained contractors duly certificated and authorised by Pattern Imprinted Concrete Supplies Ltd".

HEALTH AND SAFETY

Non-flammable and non-toxic. Sub-micronic powder, wearing of approved respirator is recommended. Refer to the Safety Data Sheet for further details.

TECHNICAL SERVICES

For further information, call our technical dept on:-
Φ UK (01635) 202224

Φ International +44(0)1635 202224

e-mail info@picsuk.com
Website www.picsuk.com

02-04-2024

Warranty

Pattern Imprinted Concrete Supplies Ltd products are guaranteed against defective materials and manufacture and are sold subject to its standard Terms and conditions of Sale, copies of which may be obtained on request. Whilst Pattern Imprinted Concrete Supplies Ltd endeavours to ensure that any advice, recommendation, specification or information it may give is accurate and correct, it cannot, because it has no direct or continuous control over where or how its products are applied, accept any liability either directly or indirectly arising from the use of its products, whether or not in accordance with any advice, specification, recommendation or information given by it.

Manufactured by:

PATTERN IMPRINTED CONCRETE SUPPLIES LIMITED
Unit 2 & 4, Red Shute Hill Ind. Est., Hermitage,
Nr Newbury, Berkshire, RG18 9QL, United Kingdom
www.picsuk.com
info@picsuk.com

