



Aquabloc

Aquabloc is a hydrated calcium silicate ceiling tile offering 100% RH performance and is suitable for use in areas subject to extremes of humidity and temperature.

Key Features

- 100% RH resistance
- Suitable for extreme temperatures and high humidity conditions
- Resistant to damage
- Ideal for spas and water parks



Edge Detail	Board																															
Thickness (mm)	6																															
Modules (mm)	600 x 600 2100M																															
Suspension Systems	Prelude 24 XL ² / TLS Prelude 24 Corrosive Resistant ¹ Clean Room 24																															
Colour	Global White																															
Sustainability	30 EN 13964 / E1																															
Acoustics	EN ISO 354 & EN ISO 11654 EN ISO 21040-9 & EN ISO 717-1 <table> <thead> <tr> <th></th><th>α_w</th><th>D_{nfw}</th><th>Class</th><th>NRC</th><th>125</th><th>250</th><th>500</th><th>1000</th><th>2000</th><th>4000</th></tr> </thead> <tbody> <tr> <td>Board</td><td>0.10(L)</td><td>37 dB</td><td>–</td><td>0.10</td><td>0.25</td><td>0.15</td><td>0.10</td><td>0.10</td><td>0.10</td><td>0.05</td></tr> </tbody> </table>											α_w	D_{nfw}	Class	NRC	125	250	500	1000	2000	4000	Board	0.10(L)	37 dB	–	0.10	0.25	0.15	0.10	0.10	0.10	0.05
	α_w	D_{nfw}	Class	NRC	125	250	500	1000	2000	4000																						
Board	0.10(L)	37 dB	–	0.10	0.25	0.15	0.10	0.10	0.10	0.05																						
Fire Reaction	Euroclass A1 EN 13501-1																															
Performances & Features	84% 100% RH 8.0 Kg/m²																															

If you would like to order a sample or have any queries about this product please contact our Technical Sales Team on **0800 371 849** or email enquiries@zentia.com

TDS 100.1.02.23