

ARBOSEAL BUTYL 88

Arboseal Butyl 88 is a round section, preformed butyl strip. It deforms under moderate pressure and has appreciable surface tack and recovery.

MAIN APPLICATIONS

Recommended for lap joints in roofing and cladding.

NB: Not recommended for use in expansion joints.

TECHNICAL DATA

Colours	Black
Application Temperature:	+ 5° C to + 50° C
Service Temperature:	- 25° C to + 50° C
Chemical Resistance:	Fair resistance to most dilute acids and alkalis, vegetable oils and alcohol. Poor resistance to hydrocarbon solvents.
UV Resistance:	Good
Service Life:	20 years +

STORAGE LIFE

36 months in original unopened packaging
stored in a cool, dry place out of direct sunlight

PACKAGING

Sizes: 6mm & 8mm

Multistrand reels; 6mm diameter =

41.3 metres/reel, 4 per box

8mm diameter = 27 metres/reel, 4 per box

HEALTH AND SAFETY

No known health hazards associated with this
product. Please consult Material Safety Data
Sheet for full information.

ACCESSORIES**Cleaners**

Arbo Cleaner No.17- 1 Litre Tin

(Xylene based – not suitable for use with plastics
or delicate finishes)

Arbo Cleaner No. 16 - 1 Litre Tin

(Alcohol Based)

IMPORTANT: The information in this leaflet is given in good faith and based on results gained from experience and tests. However, all recommendations or suggestions are made without guarantee since the conditions of use are beyond our control. Goods are supplied subject to the Company's terms and conditions of sales, a copy of which is available on request.

**UK
CA**

CARLISLE® Adshead Ratcliffe & Co. Ltd United Kingdom

Derby Road | Belper
Derbyshire

DE56 1WJ
United Kingdom

T +44 (0)1773 826661
F +44 (0)1773 821215

E info.arbo@ccm-europe.com
www.arbo.co.uk