ARBO

ARBOSEAL GZ

Arboseal GZ is a flat section, preformed butyl strip. It deforms under moderate pressure and has appreciable surface tack and recovery.

MAIN APPLICATIONS

Recommended for lap joints in roofing and cladding, guttering. Glazing units into timber frames and glazing double glazed units into externally beaded metal frames.

Caution:

- Certain Hardwood finishes and treatments may cause softening of Arboseal GZ. Please contact Adshead Ratcliffe Technical Services Department for further information.
- ii. Not recommended for use in expansion joints.

TECHNICAL DATA		
Colours	Black, White, Teak	
Application Temperature:	+ 5º C to + 50º C	
Service Temperature:	- 25º C to + 50º C	
Chemical Resistance:	Fair resistance to most dilute acids and alkalis, vegetable oils and alcohol. Poor resistance to hydrocarbon solvents.	
UV Resistance:	Good	
Service Life:	20 years +	



HEALTH AND SAFETY

No known health hazards associated with this product. Please consult Material Safety Data Sheet for full information.

ACCESSORIES

Cleaners

Arbo Cleaner No.17- 1 Litre Tin (Xylene based – not suitable for use with plastics or delicate finishes) Arbo Cleaner No. 16 - 1 Litre Tin (Alcohol Based)

PACKAGING

COLOUR	SIZE	NUMBER OF REELS/BOX
WHITE	10 x 3mm, 12 metres	20
BLACK	10 x 3mm, 12 metres	20
WHITE	12 x 3mm, 12 metres	20
BLACK	12 x 3mm, 12 metres	20
TEAK	12 x 3mm, 12 metres	20
WHITE	15 x 3mm, 12 metres	16
BLACK	15 x 3mm, 12 metres	16
TEAK	15 x 3mm, 12 metres	16
BLACK	18 x 3mm, 12 metres	12
BLACK	22 x 3mm, 12 metres	12
BLACK	35 x 3mm, 12 metres	8
BLACK	50 x 3mm, 12 metres	4
BLACK	50 x 6mm, 6 metres	4

IMPORTANT: The information in this leaflet is given in good faith and based on results gained from experience and tests. However, all recommendations or suggestions are made without guarantee since the conditions of use are beyond our control. Goods are supplied subject to the Company's terms and conditions of sales, a copy of which is available on request.