



TOP X

The surface drainage channel ideal for residential applications - driveways, courtyards, patios and garden paths



TOP X

The drainage channel for houses, courtyards, patios and gardens.

1 Requirements

Drainage channels in private areas must

- withstand the daily loadings continually.
- be easy to transport and simple to install.
- be resistant to environmental effects (frost, heat and moisture).
- be visually pleasing.

2 Application areas

- predominately residential areas
- garage entrances
- courtyard areas
- terraces
- gardens
- parks

3 Solution


Because of this the new TOP X channels are very suitable for the drainage of residential areas

- high stability and functionality
- low weight
- preformed supports for simple pipe connection
- gratings made of recycled composite, galvanised steel or stainless steel






The benefits of **TOP X** channels



Numerous design possibilities

- channels and accessories in black or silver
- different grating designs in the materials recycled composite, galvanised steel or stainless steel

= Flexibility



Locking mechanism

- boltless locking by safe clamping

= Safety



Round channel

- better hydraulic performance


= Safety



Low weight ensures easy handling on site

- significantly lighter than channels made of mineral material
- especially easy to transport and process

= Cost saving



High-quality material

- robust and unbreakable
- elastic and especially resistant recycled composite
- withstands the passage of cars

= Safety



Quick installation

- easy to process
- tongue and groove system for immediate laying
- direct paving possible

= Cost saving

TOP X


The surface drainage channel for residential applications

TOP X channels meet the requirements of DIN EN 1433 and are suitable for the following load categories:



Class A 15

TOP X channels are suitable for car traffic.



1

■ Channels made of PP recycled composite, according to EN 1433, CE-conform, with tongue and groove connection for exact installation

2

■ various grating options - made of recycled composite (black or silver), galvanised steel or stainless steel

3

■ various connection possibilities through channel or universal box with or without leaf collector and foul air trap

4

■ TOP X universal box can be used as corner unit or trash box with and without foul air trap

5

■ closed end caps

Gratings made of recycled composite or stainless steel are 100% corrosion free.




Complete accessories with assembly instruction: (available in black or silver)

for TOP X channel		for TOP X universal box		
				
<p>Connection set for channel with end caps, adapter, black, including assembly instruction, Item No. 44340</p>	<p>Connection set for channel with end caps, leaf trap, adapter, foul air trap, black, including assembly instruction, Item No. 44343</p>	<p>TOP X universal box as corner unit, including assembly instruction Item No. 44360</p>	<p>TOP X universal box, black, with connection set, end caps, leaf trap, foul air trap, including assembly instruction Item No. 44346</p>	<p>Foul air trap for TOP X universal box, Item No. 44349</p>


TOP X

TOP X, combi article, PP channel with grating, class A 15

black, with slotted grating,
galvanised



Sectional drawing of Top X



silver, with slotted grating,
galvanised




	Length mm	Width mm	Height mm	Drainage cross sec- tion cm ²	Intake cross section cm ² /m	Weight kg	Item No.
black, with slotted grating, galvanised	1000	119	89	45	256	1,9	44300
black, with slotted grating, stainless steel	1000	119	89	45	256	1,9	44303
silver, with slotted grating, galvanised	1000	119	89	45	256	1,9	44332
silver, with slotted grating, stainless steel	1000	119	89	45	256	1,9	44333

Shipment only in complete units (pallets).


TOP X

TOP X, combi article, PP channel with grating, class A 15


black, with mesh grating MW 8/21,
made of PP, black



silver, with mesh grating MW 8/21,
made of PP, silver



black, with slotted grating,
made of PP, black



	Length mm	Width mm	Height mm	Drainage cross sec- tion cm ²	Intake cross section cm ² /m	Weight kg	Item No.
black, with mesh grating MW 8/21, made of PP, black	1000	119	89	45	505	1,6	44320
silver, with mesh grating MW 8/2, made of PP, silver	1000	119	89	45	505	1,6	44325
black, with slotted cover, made of PP, black	1000	119	89	45	118	1,5	44335

Shipment only in complete units (pallets).

TOP X

TOP X Accessories



Connection set for channel with end caps, adapter, black, including assembly instruction



Connection set for channel with end caps, adapter, silver, including assembly instruction



Connection set for channel with end caps, leaf trap, adapter, foul air trap, silver, including assembly instruction



TOP X universal box as corner unit, black, including assembly instruction



TOP X universal box as corner unit, silver, including assembly instruction



TOP X universal box, black, with connection set, end caps, leaf trap, foul air trap, including assembly instruction



Foul air trap for TOP X universal box



TOP X access cover for slotted grating, galvanised

	Length mm	Width mm	Height mm	Weight kg	Item No.
Connection set for channel with end caps, adapter, black, including assembly instruction	-	-	-	0,1	44340
Connection set for channel with end caps, adapter, silver, including assembly instruction	-	-	-	0,1	44341
Connection set for channel with end caps, leaf trap, adapter, foul air trap, black, including assembly instruction	-	-	-	0,5	44343
Connection set for channel with end caps, adapter, foul air trap, silver, including assembly instruction	-	-	-	0,5	44344
TOP X universal box as corner unit, black, including assembly instruction *	137	137	125	0,2	44360
TOP X universal box as corner unit, silver, including assembly instruction *	137	137	125	0,2	44365
TOP X universal box, black, with connection set, end caps, leaf trap, foul air trap, including assembly instruction	-	-	-	0,7	44346
TOP X universal box, silver, with connection set, end caps, leaf trap, foul air trap, including assembly instruction	-	-	-	0,7	44347
Foul air trap for TOP X universal box	-	-	-	0,1	44349
TOP X access cover for slotted cover, galvanised	500	124	58	3,5	44390

*additionally required Item No. 44340, 44341, 44343 or 44344

TOP X

Quick and easy installation




Produce trench in which to lay channel with frost resistant sub base.



Fill with concrete and compress to foundation.




Produce connection openings.



Fit accessories.



Lay channels.



launch the concrete.



Install surface coating.



TOP X installation videos.



We reserve the right
to do technical changes
All drawings, Measurements
and weights are noncommittal for improvement
006-01-1214

HAURATON LIMITED

UNIT 4, FRENCHS AVENUE
DUNSTABLE, BEDFORDSHIRE
LU6 1BH

TEL: 01582 501380

FAX: 01582 501399

E.MAIL: TS-UK@hauraton.com

www.hauraton.co.uk