

Metal 1 hour fire rated access panels – picture frame

Multi performance 1 hour fire rated steel access panels featuring mineral wool and draught stripping for greatly reduced air leakage opportunities and an excellent acoustic performance.



Use

- Provides access to services and connections behind dry lined walls, ducts, ceilings where a 1 hour fire rating is required
- Projects with additional reduced air leakage and /or acoustic performance requirements
- Ideal solution for meeting Part J and the gas safety industry's concealed boiler flue inspection access requirements (1 hour fire rated applications)

Features and benefits

- Purpose made product saves time and money compared with traditional joiner-made access doors
- Fire rating independently tested by Exova Warringtonfire
- Mineral wool insulation and draught stripped to reduce the opportunity of air leakage in application
- 32mm low profile frame ideal for installation with 15mm plaster board
- Flush fitting door panels with excellent aesthetic appearance and finish
- Visible picture frame surround smartly conceals cut out edges and contributes to a faster installation
- Enduring polyester powder coated finish
- Allows for painting if required
- Quick and straightforward to install
- Universal door handing
- Hinged door panel with T-key lock mechanism and key lock
- Quick release door panel mechanism fully removes to the door for maximum access
- Acoustic performance of 33dB (contact the Timloc Technical team for more information)

Quality

- Manufactured to BS EN ISO 9001 and BS EN ISO 14001
- Helping to meet Building Regulation: - Document Part J – Concealed Flues in Voids (2010 edition)
- - Document Part E – Resistant to Sound (2003 edition)
- - Part L1 and L2 – Conservation of Fuel and Power (2013 edition)

Material and colour choice

- Electro galvanised mild steel
- Glass wool insulation (45kg/m3)
- Polyester powder coated smooth finish 20% Gloss
- White – RAL 9016

Installation advice

- Please contact the Timloc Technical team for installation advice

Care and maintenance

- Clean using a soft cloth with a mild detergent
- Spare keys available upon request

How to order

- State which size of panel is required and confirm the hole cutting size

Bill of quantity

L20 Doors/Shutters/Hatches
Clause

630^A HATCHES

- Manufacturer: Timloc Building Products, Timloc House, Ozone Park, Howden, East Yorkshire, DN14 7SD. T: 01405 765567 W: www.timloc.co.uk
- Type: Timloc Metal 1 Hour Fir Rated Access Panels - Picture Framed
- Product code: Example APC300x300CR (see other product codes/variation of sizes)
- Frame fitting size: Example 305x305mm (see other product codes/variation of sizes)
- Application: Wall, ceiling or voids
- Frame type: Picture
- Colour: White - RAL 9016 Smooth Polyester Powder Coating

Product codes

Metal 1 hour fire rated access panels with picture frame

Frame fitting size	Clear opening size	Overall panel and frame size	Door type	Product code
155 x 155mm	110 x 110mm	200 x 200mm	Hinged with T-key lock	APC150x150CR
155 x 235mm	110 x 190mm	200 x 280mm	Hinged with T-key lock	APC150x230CR
205 x 205mm	160 x 160mm	250 x 250mm	Hinged with T-key lock	APC200x200CR
305 x 305mm	260 x 260mm	350 x 350mm	Hinged with T-key lock	APC300x300CR
455 x 455mm	410 x 410mm	500 x 500mm	Hinged with T-key lock	APC450x450CR
555 x 555mm	510 x 510mm	600 x 600mm	Hinged with T-key lock	APC550x550CR
605 x 605mm	560 x 560mm	650 x 650mm	Hinged with T-key lock	APC600x600CR
150 x 150mm	110 x 110mm	200 x 200mm	Hinged with key lock	APC150x150CRKL
150 x 230mm	110 x 190mm	200 x 280mm	Hinged with key lock	APC150x230CRKL
200 x 200mm	160 x 160mm	250 x 250mm	Hinged with key lock	APC200x200CRKL
300 x 300mm	260 x 260mm	350 x 350mm	Hinged with key lock	APC300x300CRKL
450 x 450mm	410 x 410mm	500 x 500mm	Hinged with key lock	APC450x450CRKL
550 x 550mm	510 x 510mm	600 x 600mm	Hinged with key lock	APC550x550CRKL
600 x 600mm	560 x 560mm	650 x 650mm	Hinged with key lock	APC600x600CRKL