INV SNTIVE

Roof ventilation solutions

RTV-P | Plain Tile Vent

Plain roof tile vent to enable ventilation directly into a roof space or connect to a ducted ventilation system

Uses

- On roofs with Plain roof tiles
- Enables ventilation directly into a roof space
- Can also be connected to a ducted ventilation system inside the building

Features and Benefits

- Suitable for roofs with a minimum pitch of 35°
- Free ventilation area of 7,000mm²
- Sized to replace three plain tiles to provide a continuous visual appearance along the roof when viewed at all levels
- Shaped to manage and channel rainwater back down onto the roof tiles and away from the vent opening
- 4mm spaced external grille to prevent rainwater ingress and keep out large insects, vermin and debris
- UV stabilised top for continuous exposure to sunlight
- Lightweight and easy to handle

Relevant Standards

- Independently tested by BRE for deluge and wind driven rain to PD CEN/ TR15601:2012
- BS EN 490:2011 Concrete roofing tiles and fittings for roof covering and wall cladding product specifications (+A1:2017)
- BS 5250: 2021 Management of moisture in buildings Code of practice
- BS 5534:2014 Slating and tiling for pitched roofs and vertical cladding code of practice (+A2:2018)
- Manufactured to BS EN ISO 9001:2015 and BS EN ISO 14001:2015
- Complies with all relevant sections of the Building Regulations 2010
- Satisfies all relevant NHBC requirements

Compatibility

Plain tiles from all major manufacturers including:

- Redland Rosemary
- Russell Traditional Plain
- Marley Plain
- Sandtoft Humber Plain

Material and Colour Choice

- Available in Terracotta, Brown, Grey and Red
- \bullet Top UV stabilised coloured injection moulded Polypropylene with textured finish
- Base Black injection moulded Polypropylene






Terracotta RTV-PTE

Brown RTV-PBR

Grey RTV-PGR

Red RTV-PRD

Product Dimensions



Compatible Accessories

• Full datasheets available for all accessories

Description	Product Code	Product Image
110mm Flexi-Pipe to aid connection to ventilation duct or soil vent pipe	RTV-KIT1	
Plain adapter to attach the roof tile vent to 110mm ductwork	RTV-ADP	
Multi adapter (RTV-ADMULTI) to aid connection to 100/110/125/150mm duct sizes	RTV-ADMULTI	
RTV-KIT1 and RTV-ADP available as one kit	RTV-KIT3	

Airflow Test Data

RTV-P (100mm duct)					
Flow Rate I/s	Static pressure difference Pa				
5	2				
10	9				
15	19				
20	34				

Product Codes

		Color I			Durit of Contra		Deal Contra	
Product	Description	Colour	Weight	Box Quantity	Product Code	Pack Quantity	Pack Code	Pallet Quantity
Plain Roo	of Tile Vent	Terracotta	0.7kg	1	RTV-PTE	14	RTVMULTI-PTE	238
Plain Roo	of Tile Vent	Brown	0.7kg	1	RTV-PBR	14	RTVMULTI-PBR	238
Plain Roo	of Tile Vent	Grey	0.7kg	1	RTV-PGR	14	RTVMULTI-PGR	238
Plain Roo	of Tile Vent	Red	0.7kg	1	RTV-PRD	14	RTVMULTI-PRD	238

NB. RTV-P available in single, pack or pallet quantities. For pack quantities, 14 tile vent assemblies are packaged in one large box.

 Timloc Building Products, Timloc House, Ozone Park, Howden, East Yorkshire, DN14 7SD

 T: 01405 765 567
 E: sales@timloc.co.uk
 W: www.timloc.co.uk
 Technical
 E: technical@timloc.co.uk