

# **Eaves Vent**

Efficient multi-functional ventilation system

#### Use

- For roof eaves ventilation
- On roofs where the eaves incorporate a fascia board
- On roofs which do not incorporate a soffit board or where an unbroken soffit board is required

### Features and Benefits

- Provides ventilation equivalent to a continuous 10mm opening (10,000mm<sup>2</sup> per metre run) and is supplied in 1m lengths.
- Efficient, very unobtrusive and easy to fit
- Superior strength construction will carry the weight of the bottom row of tiles
- Performs several functions in a single product over fascia ventilator, felt support/eaves protector and eaves comb filler
- 4mm wide ventilation slots comply with BS 5250 : 2021
- Durable and totally resistant to decay
- UV stabilised and colourfast
- Supplied in convenient effective 1m lengths

#### Quality

- Satisfies all NHBC requirements
- Manufactured to BS EN ISO 9001 and BS IN ISO 14001
- Complies with all relevant Building Regulations
- Meets all relevant British Standards

# Material and Colour Choice

• Manufactured by injection moulding in high density polypropylene

• Available in black only

#### **Installation Advice**

- Use to ventilate pitched roofs, where the pitch of the roof is 15 degrees or more, and the roof void is attic or loft space
- Make sure each ventilator is fixed securely into the top of the fascia board using screws or nails through the fixing holes provided
- Products designed so that the roofing felt will be cut back flush with the edge of the fascia board, and not dressed out into the gutter
- Ventilation must be provided for the full length of the eaves and along both sides of the building to create a cross flow ventilation action

Please see technical section for more details.

# How to Order

- Specify product code with C if integral eaves comb filler is needed
- Measure the overall length of the eaves to be ventilated and divide by 1000mm to determine the number of ventilators required

# **Bill of Quantity**

#### Eaves Vent

G20 Carpentry/Timber Framing/First Fixing Clause

910<sup>^</sup> EAVES SOFFIT VENTILATION

- Manufacturer: Timloc Building Products, Timloc House, Ozone Park,
- Howden, East Yorkshire, DN14 7SD. T: 01405 765567 W: www.timloc.co.uk • Product Reference: 3014C or 3014
- Type: Over Fascia Ventilation System (1000mm) 10mm Airflow
- Colour: Black
- Airway: Provide the equivalent of a continuous opening of not less than 10mm for the full length of eaves.



#### **Environmental Product Declaration**


A quantification of environmental information regarding the life cycle of the Eaves Vent. GWP total is for production stages A1-A3. Verified in accordance with ISO 14025. View the full EPD at timloc.co.uk.


Product	EPD Reference	EPD Mass (KG)	GWP A1-A3 (KG CO2e)
3014	EPD HUB, HUB-1836	0.47	1.18E-02
3014C	EPD HUB, HUB-1836	0.526	1.32E-02

### **Product Codes**

Free Airflow	Length	Eaves Comb	Pack Qty	Product Code
10,000mm <sup>2</sup> per meter	1m	Yes	10	3014C
10,000mm <sup>2</sup> per meter	1m	No	20	3014

#### Product Dimensions





Timloc Building Products, Timloc House, Ozone Park, Howden, East Yorkshire, DN14 7SD T: 01405 765 567 E: sales@timloc.co.uk W: www.timloc.co.uk Technical | E: technical@timloc.co.uk