
timloc building products

AIRBRICK
DATASHEET



Airbrick ventilator available in a range of colours

Use

- In conjunction with the 1201/1201XL/1201XL+ telescopic underfloor vent for providing ventilation below suspended ground floors.
- In conjunction with cavity sleeves for ventilation through external walls to a building interior.

Features & Benefits

- Equivalent area of 6170mm² per air brick.
- Unique stepped front grille greatly reduces the entry of wind driven rain.
- 6.5mm wide front grille openings comply with BS 5440 Pt 2 and British Gas requirements.
- Integral clip together facility allows multiple airbricks to be stacked to form 9" x 6" and 9" x 9" sizes.
- Available in a range of colours to blend in with various brick types.
- Very tough and robust.
- Durable and totally resistant to decay.

Quality

- Satisfies all NHBC requirements.
- Manufactured to BS EN ISO 9001 and BS EN ISO 14001.
- Complies with all relevant Building Regulations.
- Meets all relevant British Standards.
- Equivalent area marking to front face of airbrick to comply with BS EN 13141-1 : 2004.

Material & Colour

- Injection moulded Polypropylene.
- Available in Buff, Terracotta, Grey, Brown, Black, White and Blue Black.

How to Order

- Airbrick quantity will be relative to the number of telescopic underfloor ventilators or cavity sleeves required.
- State the colour required.

Environmental Product Declaration

A quantification of environmental information regarding the life cycle of the Airbrick. GWP total is for production stages A1-A3. Verified in accordance with ISO 14025. View the full EPD at timloc.co.uk.

Product	EPD Reference	EPD Mass (KG)	GWP-fossil, A1-A3 ($kgCO_2e$)
1201ABWH	HUB-2180	0.118	2.253E-01
1201AB	HUB-1836	0.1	4.840E-02

Bill of Quantity

F30 Accessories/sundry items for brick/block/stone walling Clause 160 | AIRBRICK

- To BS493, Class 1, built in as the work proceeds.
- Manufacturer: Timloc Building Products, Timloc House, Ozone Park, Howden, East Yorkshire, DN14 7SD. T: 01405 765567, W: www.timloc.co.uk
- Reference: 1201AB
- Design: Rectangular
- Work size: Each unit 69mm coursing x 215mm,
- (Equivalent area 6170mm²)
- Material: Thermoplastic
- Colour: (Black, White, Brown, Buff, Grey, Blue Black or Terracotta)
- Optional Accessories: e.g. 1201 Telescopic Under Floor Vent (6,500mm² with Airbrick)

Installation Advice

- Always use in conjunction with a Timloc telescopic underfloor ventilator, or cavity sleeve, depending on the application

Product Codes

Description	Height	Width	Length	Colour	Equivalent Area	Pack Quantity	Lead Time	Product Codes
Airbrick	69mm	60mm	215mm	Blue Black	6170mm²	20	Next Working Day	1201ABBB
Airbrick	69mm	60mm	215mm	Black	6170mm²	20	Next Working Day	1201ABBL
Airbrick	69mm	60mm	215mm	Brown	6170mm²	20	Next Working Day	1201ABBR
Airbrick	69mm	60mm	215mm	Buff	6170mm²	20	Next Working Day	1201ABBU
Airbrick	69mm	60mm	215mm	Grey	6170mm²	20	Next Working Day	1201ABGR
Airbrick	69mm	60mm	215mm	Terracotta	6170mm²	20	Next Working Day	1201ABTE
Airbrick	69mm	60mm	215mm	White	6170mm²	20	Next Working Day	1201ABWH