QUICK DRY WOOD PRIMER UNDERCOAT

Dulux Trade Quick Dry Wood Primer Undercoat is a water-based, high opacity, dual purpose primer undercoat for interior and exterior woodwork, which is recoatable in 2-4 hours. It is ideal for use as a primer for softwoods, hardwoods, chipboard and fibre board (except fire retardant-treated types). **Dulux Trade Quick Dry Wood Primer Undercoat** can also be used as an undercoat for woodwork that has been previously primed or painted with either solvent- or water-based paint.

Accreditations

BREEAM Compliant	LEED Compliant	WELL Compliant	EPD Available
✓	✓	✓	✓

This product has been independently tested by Eurofins, following the Indoor Air Comfort Gold test which is based on ISO 16000 / EN 16516, for Formaldehyde, Total Volatile Organic Compounds (TVOCs) and Carcinogens. It is BREEAM NC 2018 & LEED v4.1 compliant and contributes toward satisfying Feature X06 (VOC restrictions) under the WELL Building Standard®. For further information please visit the 'Datasheets and Documents' section of the specific product page at duluxtrade.co.uk

KEY BENEFITS

- 2-in-1
- For Softwoods & Hardwoods
- Provides Excellent Adhesion

PRODUCT INFORMATION

Typical Use

Suitable for use on interior and exterior soft and hardwoods. Not recommended as a primer for metal, plaster, brickwork, rendering, asbestos, cement or rough surfaces. Do not use on heated surfaces.

Pack Size

1L, 2.5L and 5L.

Colour Range

White only.

Composition (nominal)

Pigment: Non Lead Pigments.
Binder: Acrylic Copolymer.
Solvent: Water.

Volume Solids

36% (nominal).

SURFACE PREPARATION

To get the best results, ensure surfaces to be painted are sound, clean and dry (new surfaces particularly must be fully dry) and free from all defective or poorly adhering material such as dirt, grease or wax.

Thoroughly rub down previously painted surfaces, using 'wet flatting' methods where possible, then wipe off with a damp, lint free cloth. Special precautions should be taken during surface preparation of pre-1960s paint surfaces over wood and metal as they may contain harmful lead.

Treat any knots in wood with an appropriate knotting solution.

Any surface defects should be filled with the appropriate **Polycell** Trade **Polyfilla.**

SYSTEMS INFORMATION

STIR THOROUGHLY BEFORE USE.

New or bare surfaces: 2 coats of **Dulux Trade** Quick Dry Wood Primer Undercoat.

Previously painted surfaces: 1 coat of **Dulux Trade** Quick Dry Wood Primer Undercoat.

Allow to dry for a minimum of 2 hours between coats, then apply an appropriate **Dulux Trade** paint system.

APPLICATION METHOD

Brush, roller and airless sprays.

Do not use when the temperature falls below 10ºC or outside when there is a likelihood of rain.

QUICK DRY WOOD PRIMER UNDERCOAT

Practical Coverage

A guide to the practical coverage which can be achieved under normal conditions is up to 13m² per litre.

Thinning

Sealing new or bare surfaces: Add up to 1 part clean water to 5 parts paint.
Normal use (not to be exceeded): Add up to 1 part clean water to 10 parts paint.
Airless spray application: Add up to 1 part clean water to 5 parts paint.

Spray Recommendations

Airless Spray: A typical set up for airless spray application would be a minimum working pressure on paint of 133 bars (2000 lb/sq in) with a spray tip size of 0.43mm (17 thou) and a spray tip angle of 60º.

Drying Times

Single coat at standard thickness:
Touch Dry: Dependent on temperature and humidity.
Recoat: 2-4 hours.

Responsible Cleaning

Cleaning After Final Use: Cleaning your brushes and rollers immediately after their final use ensures they can be reused for multiple projects, saving you money and reducing waste.
Cleaning:

1. **Remove Excess Paint:** Scrape off excess paint into container for future projects.
2. **Clean with Warm, Soapy Water:** Use warm, soapy water in a sealed container, such as a bucket or empty tub, to clean your brushes and rollers.
3. **Rinse Thoroughly:** Ensure all soap and paint residues are completely rinsed out into container.
4. **Dry Naturally:** Allow brushes and rollers to dry naturally and store them in a dry, dust-free place.
5. **Allowing solids to settle:** Allow the paint solids to settle at the bottom of the container. Once settled, pour the clear water into another container for reuse or disposal.
6. **Responsible Disposal:** Let the remaining paint solids dry out completely and dispose of them as solid waste.

Do not flush paint down the drain, including when cleaning painting tools
For professional cleaning tips, check out this video created in partnership with the British Coatings Federation and Dulux Connect contractor Bagnall's: https://coatings.org.uk/general/custom.asp?page=HowToCleanPaintbrushes

When this paint container is empty please ask your stockist about recycling. If you have leftover paint, please dispose of it responsibly and consider donating it to **Community RePaint**. Find out more at ***duluxtrade.co.uk/sustainability.***

Transportation & Storage

Do not use or store in extremes of temperature and protect from frost. To prevent spillage, please store and transport upright.

VOC

EU limit value for this product (cat.: A/d): 130g/l (2010). This product contains max. 30g/l VOC. VOC content: Low (0.30-7.99%).

FURTHER SUPPORT

If you need further support, please contact the **AkzoNobel** Technical Advice Centre on 0333 222 70 70.

Always read full Health, Safety & Environmental Information on can before use.

Safety datasheet is available free on request by telephoning the **AkzoNobel** Technical Advice Centre or by visiting ***duluxtrade.co.uk.***

AkzoNobel, the AkzoNobel logo, the Flourish logo, Dulux Trade, Polycell, Polyfilla, Community RePaint and the Planet Possible logo are trademarks of the AkzoNobel group. © AkzoNobel 2023.

QUICK DRY WOOD PRIMER UNDERCOAT

Planet Possible™

At **Dulux Trade**, we believe by working with our customers we can reduce waste and do more with the resources we have. Together we can create a better future for our planet. Join us at ***duluxtrade.co.uk/pp***