

Delta Membrane Systems Ltd Ancillary Products



DELTA PLUGS

Provides a fixing point for Delta MS 500 membrane. Delta fixing plugs have a centrally located internal shank which accommodates a 5.5mm dia./size 12 screw at a maximum depth of 30mm.

DMS 014

Box of 100



FLEXI-DRI PLUS PLUGS

These plugs have a centrally located internal shank that can accommodate a 5mm dia./size 10 screw at a maximum depth of 30mm.

DMS 230

30x of 100



QWIK-SEAL PLUGS

A watertight self-sealing fixing plug suitable for MS 500 & PT membranes. These plugs have a centrally located internal shank that can accommodate a 5mm dia./size 10 screw at a maximum depth of 30mm.

DMS 131

Box of 100



ULTRA FIX PLUGS (FIRE RETARDANT)

Delta Ultra Fix plugs are specifically designed to fix and secure Delta MS 500 Fire Retardant Membrane. Delta Ultra Fix Plugs offer a tailormade maximum hold for ease of installation. These plugs have a centrally located internal shank that can accommodate a 5mm dia./size 10 screw at a maximum depth of 30mm.

| DMS 051 | Box of 200 |
|---------|--------------------------|
| DMS 050 | Box of 200 with Grommets |



PT PI UGS

A watertight self-sealing fixing plug which works in harmony with our PT or PT 3mm membranes. Delta PT Plugs are available with grommets. Grommets allow for a watertight, self-sealing finish.

| DMS 015-1 | Box of 200 |
|-----------|--------------------------|
| DMS 133-1 | Box of 200 with Grommets |



ROPF

A dependable sealing for Delta fixing Plugs which do not have grommets. Delta Rope is ideal for sealing joints in MS20 and in stud to stud joints.

DMS 011

4.75m x 10mm



DOUBLE SIDE TAPE

This strong and durable double sided butyl tape is ideal for sealing membranes together at overlaps/adjacent seals.

DMS 012

22.5m x 28mm



CORNER STRIP

A waterproof, firm, and lasting single-sided sealing tape, typically used for sealing and connecting membranes on joints/wall floor junction or overlap.

DMS 020

150mm x 20m



FIRE RETARDANT FLEECE TAPE

A high-performance fire retardant fleece backed butyl waterproof sealing tape for butt joints and overlapping of membranes.

DMS 852

1mm x 220mm x 20m



FLEECE TAPE

Designed for use with our Delta PT membrane. Suitable for joint sealing, detailing around service penetrations where Delta PT membranes have been installed.

DMS 238

100mm x 20m



MS CLIPS

Delta MS Clips are used for external waterproofing applications where a external drainage and protection membrane is installed.

DMS 099

MS Clip



MS PROFILE STRIPS

Delta MS Profile Strip is used in external waterproofing applications as a capping strip where an external drainage and protection membrane is installed

DMS 017

2m lenath



PT PROFILE STRIPS

Delta PT Profile Strip is used in applications where a Delta PT membrane is installed above ground.

DMS 016

2m length



DELTA THAN

Delta Than is a superior waterproof mastic which is suitable for sealing joints and detailing.

DMS 019

310ml



DELTA FIX ADHESIVE

Formulated as an adhesive for bonding & anchoring most building materials e.g. brick, stone, steel, mortar & timber.

| DMS 018 | 400ml (fix adhesive) |
|---------|---------------------------|
| DMS 044 | Fiz Mixer Nozzles |
| DMS 043 | Twin Cartridge Applicator |



DRILL BITS

Fully ground, straight shank drill bit. For drilling fixing plugs to Delta membranes.

| DMS 076 | 8mm |
|---------|------|
| DMS 075 | 9mm |
| DMS 041 | 10mm |
| DMS 042 | 11mm |



PUDDLE FLANGE

A Delta Puddle Flange offers a waterproof seal when applying Delta Modular Drainage. A Delta Puddle Flange prevents ground water percolating up between the 110mm pipe work/RC slab or wall junction, reducing water ingress through the critical floor/wall junctions.

| DMS 162 | 50mm |
|---------|----------------------------------------------------|
| DMS 161 | 110mm (various sizes available from 32mm to 160mm) |



GL2 BRACKETS

GL2 Drylining Bracket/Gyplyner brackets. This adjustable metal bracket helps create a firm & rigid background when lining old masonry walls. The clever but simple bracket is pre-drilled for quick fitting, and is designed to be easily bent to provide extra adjustment.

| DMS 049 | Box of 100 |
|---------|------------|
| JMS 049 | I DOY OLTO |
| | |



JOIST BOOTS / TOP HATS

Solving long standing problems, Delta "boots" steel joist end "top hats" make a real difference in structural waterproofing situations where steels are embedded in walls, in below ground sections of structures. Available in any size, as we make these to order with a 3-5 day turn around.

- · Made to order
- · Protects Steel Joists
- · Prevents Steel joists from rusting
- Continuous waterproofing when used in conjunction with waterproofing solutions

SPECIAL ORDER



Delta House, Merlin Way, North Weald, Epping, Essex CM16 6HR Tel: +44 (0)1992 523 523 info@deltamembranes.com www.deltamembranes.com