

Screenzone Recessed Air Curtains - RAC1306, RAC1309, RAC1312, RAC1509, RAC1512, RAC1514 & RAC1516

6kW, 9kW, 12kW, 14kW & 16kW

Designed to fit above a doorway in a suspended ceiling, the Recessed Screenzone provides a discreet welcoming curtain of warmth for doorways in shops, hotels, offices and commercial premises. Overall energy savings are likely when the heater is sited above a frequently opened external door as the airstream can prevent heat loss.

- 6kW, 9kW, 12kW, 14kW or 16kW rating
- Will fit a recess as shallow as 230mm (175mm unit depth plus 55mm free air)
- Energy efficient brushless motor.
- Supplied with HE8408 remote switch.
- Multiple heaters can be controlled from one switch.
- Optional ACMC (Air Curtain Master Controller) and ACTS (Air Curtain Temperature Sensor) available.
- ACTS must be used in conjunction with ACMC.
- 2 heat settings, 2 fan speeds with remote switch.
- 8 heat settings, 8 fan speeds with optional ACMC.
- Fan only setting for air circulation.
- Automatic safety cut-out for thermal overload protection.
- Compatible with Building Management Systems.
- Finished in white.



Dimensions (mm) & Weight (kg):

Model No.	Depth	Width	Length	Weight
RAC1306 / RAC1309 / RAC1312	175	339	1350	19.5
RAC1509 / RAC1512 / RAC1514 / RAC1516	175	339	1550	21.0

Model No.	kW	Max Mounting Height (m)	dBA	Single Phase	3 Phase
RAC1306	6	2.8	60	•	•
RAC1309	9	3.4	60	•	•
RAC1312	12	3.4	62		•
RAC1509	9	3.4	62		•
RAC1512	12	3.4	62		•
RAC1514	14	3.4	62		•
RAC1516	16	3.4	62		•

Note: dBA readings are taken at 3 meters from the heater in a free field environment.