

PLE-RF - Electronic 7-Day Timer Panel Heaters with RF Receiver

For Multizone Heating System

Our new range of electronic 7-day timer heaters can be connected to a multizone heating system. Each heater has an RF receiver which communicates with the central control unit, MRX1 Multizone wireless controller. Each MRX1 controller can control up to 8 heaters.

The PLE panel heaters feature an electronic timer which offers a 7-day programme with 6 heating periods per day. The digital control panel has an easy-to-read display and four large control buttons with tactile feedback. Easy to operate and designed with an electronic lock to prevent tampering with controls. Features open window detection which recognises a sudden temperature drop when a window is opened and turns the heating off to save energy. Once the window is closed, the temperature change triggers the heating to resume its normal operation. These slimline heaters with concealed digital controls have strengthened grilles to increase durability and feature a snap-on bracket on their wall mounting system which allows easy installation and dismounting for cleaning and decorating. Ideal for hotels, offices, bedrooms, kitchens, bathrooms and laundries.

- Available in 0.5kW, 0.75kW, 1kW, 1.25kW, 1.5kW and 2kW
- Compatible with MRX1 wireless controller
- 7-day timer with electronic thermostat
- 6 heating periods per day
- Very quiet operation
- Open window detection
- Copy day function
- Concealed digital controls
- 4 operating modes: Programme, Boost, Setback & Manual
- 15-minutes Boost feature
- Comfort heat between 15°C to 35°C
- Setback temperatures can be used for frost protection or maintaining a minimum room temperature between 4°C to 15°C
- Automatic safety cut-out
- Can set temperatures in degrees Celsius or Fahrenheit
- Maintains temperature within 0.7 degrees
- Easy-to-read display
- Easy operation
- 4 large control buttons with tactile feedback
- Electronic child lock
- Optional control panel locking kit (PLK1)
- Slimline and clean design
- Splash proof to IP24 for use in bathrooms and other damp areas
- Hinged wall mounting system for easy installation and decorating
- Fitted with 1.1m of supply cable
- Finished in white and stainless steel



Dimensions (mm) & Weight (kg):

Model No.	Rating (kW)	Height	Depth	Width	Weight
PLE050RF	0.5	430	93	442	4.0
PLE075RF	0.75	430	93	442	4.0
PLE100RF	1	430	93	614	5.0
PLE125RF	1.25	430	93	720	6.0
PLE150RF	1.5	430	93	720	6.0
PLE200(SS)RF	2	430	93	852	6.5

Note: (SS) denotes Stainless Steel.