

# LSTE-RF LST Electronic 7-Day Timer Panel Heaters with RF Receiver

## For Multizone Heating System

Our new range of electronic 7-day timer heaters can be connected to a multizone heating system. Each heater has an RF receiver which communicates with the central control unit, MRX1 Multizone wireless controller. Each MRX1 controller can control up to 8 heaters.

The LSTE panel heaters feature an electronic timer which offers a 7-day programme with 6 heating periods per day. Features open window detection which recognizes a sudden temperature drop when a window is opened and turns the heating off to save energy. Once the window is closed, the temperature change triggers the heating to resume its normal operation. These slimline heaters are designed with a maximum surface temperature of 43°C, complying with NHS Estates Health Guidance Notes, to minimise the risk of burn injuries. They are perfect for environments with vulnerable people such as children and elderly residents; and therefore ideal for schools, nurseries, retirement homes, hospitals and anywhere where safety is paramount.

- Available in 0.5kW and 0.8kW
- Compatible with MRX1 wireless controller
- Maximum surface temperature of 43°C to comply with NHS Estates Health Guidance Notes
- 7-day timer with electronic thermostat
- 6 heating periods per day
- Very quiet operation
- Open window detection
- Copy day function
- Concealed digital controls
- 4 operating modes: Programme, Boost, Setback & Manual
- 15-minutes Boost feature
- Comfort heat setting between 15°C to 35°C
- Setback temperatures can be used for frost protection or maintaining a minimum room temperature between 4°C to 15°C
- Automatic safety cut-out
- Can set temperatures in degrees Celsius or Fahrenheit
- Maintains temperature within 0.7 degrees
- Easy-to-read display
- Easy operation
- 4 large control buttons with tactile feedback
- Electronic child lock
- Optional control panel locking kit (PLK1)
- Slimline and clean design



- Splash proof to IP24 for use in bathrooms and other damp areas
- Hinged wall mounting system for easy installation and decorating
- Fitted with 1.1m of supply cable
- Finished in white

### Dimensions (mm) & Weight (kg):

Model No.	Rating (kW)	Height	Depth	Width	Weight
LST500ERF	0.5	430	93	832	6.3
LST800ERF	0.8	430	93	1195	8.7