

# PLSTiE-RF Slimline LST Fan Heaters with RF Receiver

## With Electronic 7-Day Timer and Intelligent Fan Control

### For Multizone Heating System

Our new range of electronic 7-day timer heaters can be connected to a multizone heating system. Each heater has an RF receiver which communicates with the central control unit, MRX1 Multizone wireless controller. Each MRX1 controller can control up to 8 heaters.

Features open window detection which recognises a sudden temperature drop when a window is opened and turns the heating off to save energy. Once the window is closed, the temperature change triggers the heating to resume its normal operation. The intelligent fan control optimises fan speed and heat output to quickly achieve and control a comfort temperature whilst maintaining a very low noise level.

These heaters are designed with a maximum surface temperature of 43°C, complying with NHS Estates Health Guidance Notes, to minimise the risk of burn injuries. Ideal for nurseries, hospitals and retirement homes, these fan heaters provide a high level of safety and controllability.

- Available in 0.5kW, 0.75kW, 1kW and 1.5kW
- Compatible with MRX1 wireless controller
- Safety monitoring: Heaters now have a built-in safety monitoring feature. In the unlikely event of a fault, the safety monitoring will help prevent high surface temperatures and the heaters will beep at different intervals to indicate the type of failure. The safety monitoring will identify overheating, fan failure and certain electronic faults.
- Intelligent fan control: The fan speed of the heater automatically adjusts relative to the room's current temperature in order to achieve a warm airflow temperature. This eliminates the heater from blowing cold air when initially powered on in a cold room.
- Incorporates EC motor for improved energy efficiency
- Maximum surface temperature of 43°C to comply with NHS Estates Health Guidelines Notes
- 7-day timer with electronic thermostat
- 6 heating periods per day
- Quiet operation
- Open window detection
- Copy day function
- Concealed digital controls
- 4 operating modes: Programme, Boost, Setback & Manual
- 15-minutes Boost feature
- Comfort heat setting between 15°C to 35°C
- Setback temperatures can be used for frost protection or maintaining a minimum room temperature between 4°C to 15°C
- Automatic safety cut-out
- Can set temperatures in degrees Celsius or Fahrenheit
- Maintains temperature within 0.7 degrees
- Easy-to-read display
- Easy operation
- 4 large control buttons with tactile feedback
- Electronic child lock to prevent tampering with controls
- Optional control panel locking kit (PLK1)
- Slimline and clean design
- Splash proof to IP24 for use in bathrooms and other damp areas
- Hinged wall mounting system for easy installation and decorating
- Fitted with 1.1m of supply cable
- Finished in white



### Dimensions (mm) & Weight (kg):

Model No.	Rating (kW)	Height	Depth	Width	Weight	dBA
PLSTi050ERF	0.5	430	93	506	4.5	30
PLSTi075ERF	0.75	430	93	506	4.5	30
PLSTi100ERF	1	430	93	640	6.0	31
PLSTi150ERF	1.5	430	93	892	8.0	33