

Air Curtains Summary

- ✿ Fitted with integral switches with option for remote switch HE8407
- Supplied with remote switch
- ▲ Supplied with Electronic Controller and temperature sensor
- RX models require single zone controllers to operate

Rating (kW)	Model	Control/ Switch	Max Mtg Height(m)	Height (mm)	Depth (mm)	Width (mm)	Weight (kg)	Heat Settings	Fan Speeds	dBA	Single/ 3 Phase
3.0	HE7402	✿	2.3	210	115	634	5.1	3	1	46	Single
3.0	HE7402RX	■	2.3	210	115	634	5.1		1	46	Single
4.5	HE7420	✿	2.3	210	115	634	5.1	3	1	46	Single
4.5	HE7420RX	■	2.3	210	115	634	5.1		1	46	Single
4.5	HE8320	✿	2.3	210	115	1040	8.8	3	1	49	Single
4.5	HE8320RX	■	2.3	210	115	1040	8.8		1	49	Single
6.0	HE7426	✿	2.3	210	115	1040	8.8	2	1	49	Single
6.0	HE7426RX	■	2.3	210	115	1040	8.8		1	49	Single
6.0	HE8326	●	2.8	210	115	1040	10.3	2	2	55	Single/3 Phase
9.0	HE7433	●	2.8	210	115	1040	10.3	2	2	55	Single/3 Phase
9.0	CA1309S	●	3.4	264	205	1305	18.0	2*	2*	60	Single/3 Phase
9.0	CA1509S	●	3.4	264	205	1530	20.0	2*	2*	60	3 Phase
12.0	CA1312S	●	3.4	264	205	1305	18.0	2*	2*	60	3 Phase
12.0	CA1512S	●	3.4	264	205	1530	20.0	2*	2*	60	3 Phase
14.0	CA1514S	●	3.4	264	205	1530	20.0	2*	2*	60	3 Phase
16.0	CA1516S	●	3.4	264	205	1530	20.0	2*	2*	60	3 Phase
15.0	CA2015S	●	3.4	264	205	1970	25.0	2*	2*	60	3 Phase
18.0	CA2018S	●	3.4	264	205	1970	25.0	2*	2*	60	3 Phase
Rating (kW)	Model	Control/ Switch	Max Mtg Height (m)	Depth (mm)	Width (mm)	Length (mm)	Weight (kg)	Heat Settings	Fan Speeds	dBA	Single/ 3 Phase
3.0	RAC0603	●	2.8	155	339	634	9.5	3	1	55	Single
3.0	RAC0603RX	■	2.8	155	339	634	9.5		1	55	Single
4.5	RAC0604	●	2.8	155	339	634	9.5	3	1	55	Single
4.5	RAC0604RX	■	2.8	155	339	634	9.5		1	55	Single
6.0	RAC1006	●	2.8	155	339	985	13.5	3	1	57	Single
6.0	RAC1006RX	■	2.8	155	339	985	13.5		1	57	Single
6.0	RAC1306	●	2.8	175	339	1350	19.5	2*	2*	60	Single/3 Phase
6.0	RAC1306RX	■	2.8	175	339	1350	20.0		1	60	Single/3 Phase
9.0	RAC1309	●	3.4	175	339	1350	19.5	2*	2*	60	Single/3 Phase
9.0	RAC1509	●	3.4	175	339	1550	21.0	2*	2*	62	3 Phase
12.0	RAC1312	●	3.4	175	339	1350	19.5	2*	2*	62	3 Phase
12.0	RAC1512	●	3.4	175	339	1550	21.0	2*	2*	62	3 Phase
14.0	RAC1514	●	3.4	175	339	1550	21.0	2*	2*	62	3 Phase
16.0	RAC1516	●	3.4	175	339	1550	21.0	2*	2*	62	3 Phase
8.0-12.0	RAC10HL	▲	4.0	270	515	1082	34.0	8	8	60	3 Phase
12.0-18.0	RAC15HL	▲	4.0	270	515	1592	51.0	8	8	61	3 Phase
16.0-24.0	RAC20HL	▲	4.0	270	515	2102	68.0	8	8	62	3 Phase

* 8 heat settings, 8 fan speeds with optional ACMC.

Note: dBA readings are taken at 3 metres from the heater in a free field environment. For cable sizes, see page 47.