Screenzone Surface Mounted Air Curtains - Wireless Controlled

A welcoming curtain of warmth in shops, hotels, offices and other commercial premises with the added benefit of energy saving and comfort control.

- 3kW, 4.5kW or 6kW rating
- 634mm and 1040mm widths
- Wall mounting bracket supplied for ease of installation and angular adjustment
- Suspended, wall or trunking mounted
- Wireless controlled by a separately purchased advanced single zone controller
- Choice of wireless controllers:
  - CRXSL
  - CRXSLWIFI
  - HRXSL
  - LC
- All controllers can operate multiple RX heaters
- Fan only setting for air circulation
- Automatic safety cut-out for thermal overload protection
- Finished in white



Model No.	Rating (kW)	Type	Max Mounting Height (m)	dBA
HE7402RX	3	Single door	2.3	46
HE7420RX	4.5	Single door	2.3	46
HE8320RX	4.5	Double door	2.3	49
HE7426RX	6	Double door	2.3	49

Dimensions (mm) & Weight (kg):

Model No.	Height	Depth	Width	Weight
HE7402RX/HE7420RX	210	115	634	5.1
HE8320RX/HE7426RX	210	115	1040	8.8

Note: Only 200mm clearance from ceiling required.

Note: dBA readings are taken at 3 meters from the heater in a free field environment.