

# Cantilever Platform Lift



Fully compliant with the Machinery Directive 2006/42/EC

The Cantilever Platform Lift is mounted in a pit at the foot of the staircase, so when not in use it is flush with the surrounding floor. With a touch of a button, the Cantilever Platform Lift will rise out of the floor and over the steps until it reaches the next level. It can then be lowered back into the pit using the control panel.

This is an innovative space-saving solution which can overcome architectural barriers without having to make structural changes and can blend in discreetly with its environment.

# Cantilever Platform Lift

## Standard Features

Suitable for indoor and outdoor installation  
Safety kerb all around the platform  
Safety edge beneath the platform  
Overload detector  
Landing hold to run push button

## Optional Features

Remote Control fobs for use on lift

## Specifications

Drive	Hydraulic
Capacity	400kg
Speed	0.1m/s
Travel	Max 1m rise, 1.5m going (approx)

### SPACE REQUIREMENT / FLOOR APERTURE

Pit	230mm
-----	-------

### SIZE (bespoke sizes available)

Platform size is dependent on travel

### LIFTING PLATFORM

Flooring	Empty tray to allow flooring by others
----------	--

### ELECTRICAL DETAILS / POWER REQUIREMENT

Supply:	Dedicated 16 amp
---------	------------------