



## COMPACT FLOOR STANDING WATER COOLER

PRODUCT CODE

**A511105F**

MAY 2010



### Special Features

- ▲ HYGIENIC VANDAL RESISTANT DESIGN
- ▲ DURABLE GRANITE EFFECT SHROUD
- ▲ GLASS FILLER OPTION

### Description

The compact water cooler is self-contained, vandal resistant, mains fed and provides 18.9 litres per hour of chilled water from 26.7°C to 10°C. The cooler is supplied as standard with a flexible non-squirt design bubbler valve activated by an internally mounted self closing push button valve. A glass filler may be provided in addition to the bubbler valve.

### Construction

The top of the water cooler is manufactured from grade 304 stainless steel and incorporates an integral waste outlet. The shroud is manufactured from galvanised steel with a granite powder coated finish. As an option a stainless steel shroud manufactured from 304 grade stainless steel can be provided to special order.

The evaporator is an insulated copper tube on a stainless steel tank. The refrigerant is R-134a and is capillary tube controlled.

### Electrical Supply

The water cooler is supplied with a lead and plug for connection to a 13 amp socket

### Certification

The water cooler complies with ANSI/NSF 61, section 9 and with the Air Conditioning and Refrigeration Institute Standard 1010.

### Options

- ▲ Granite effect coated steel shroud (illustrated)
- ▲ Stainless Steel Shroud (to special order only)
- ▲ Glass Filler (in addition to the bubbler)
- ▲ Water Filter (easy twist fit, carbon block cyst system)
- ▲ 115v / 60Hz compressor available (export models)
- ▲ larger capacity 30.3 litres/hour model (611108F) available

### Order Codes and Technical Specification

Please refer to the Technical Specification Sheet

