



COMPACT FLOOR STANDING WATER COOLER

PRODUCT CODE

A511105F

MAY 2010



Special Features

- ▲ HYGIENIC VANDAL RESISTANT DESIGN
- ▲ DURABLE GRANITE EFFECT SHROUD
- ▲ GLASS FILLER OPTION

Description

The compact water cooler is self-contained, vandal resistant, mains fed and provides 18.9 litres per hour of chilled water from 26.7°C to 10°C. The cooler is supplied as standard with a flexible non-squirt design bubbler valve activated by an internally mounted self closing push button valve. A glass filler may be provided in addition to the bubbler valve.

Construction

The top of the water cooler is manufactured from grade 304 stainless steel and incorporates an integral waste outlet. The shroud is manufactured from galvanised steel with a granite powder coated finish. As an option a stainless steel shroud manufactured from 304 grade stainless steel can be provided to special order.

The evaporator is an insulated copper tube on a stainless steel tank. The refrigerant is R-134a and is capillary tube controlled.

Electrical Supply

The water cooler is supplied with a lead and plug for connection to a 13 amp socket

Certification

The water cooler complies with ANSI/NSF 61, section 9 and with the Air Conditioning and Refrigeration Institute Standard 1010.

Options

- ▲ Granite effect coated steel shroud (illustrated)
- ▲ Stainless Steel Shroud (to special order only)
- ▲ Glass Filler (in addition to the bubbler)
- ▲ Water Filter (easy twist fit, carbon block cyst system)
- ▲ 115v / 60Hz compressor available (export models)
- ▲ larger capacity 30.3 litres/hour model (611108F) available

Order Codes and Technical Specification

Please refer to the Technical Specification Sheet

